110000 Lbs. Heavy Duty Rotator Wrecker Body With Continuous Rotation Recovery Boom

Basic Information

Place of Origin: Hubei, China
Brand Name: iTruck
Minimum Order Quantity: 1

• Price: \$65000/units

• Packaging Details: Nude, covered with protection film

Delivery Time: 75 daysSupply Ability: 5 unit/month



Product Specification

Product Name: Rotator

Dimensions (L X W X H)
 Custom Made To Fit Your Truck

(mm):

• Condition: New

• Drive Type: 8*6 Driving/10x6 Driving

WheelBase: As Required
Main Winch: 25 Tons, 2 Pcs
Auxiliary Winch: Optional
Underlift: G70, 3 Sections

Underlift: G70, 3 SectionsBoom: G70, 3 Sections

Remote Control: WirelessHydraulic: DOT CertifiedWarranty: 3 Year

• Highlight: 110000 Lbs Heavy Duty Rotator,

110000 Lbs Rotator Wrecker, Rotation Boom Rotator Wrecker



More Images







Product Description

Product Description

The rotator series has different capacities from 20 tons to 100 tons.

MAXIMUM STABILITY FOR MAXIMUM PERFORMANCE.

The strength and stability of the 50 tons rotator comes from the industry-leading scissor-style outriggers and unique frame design. The rotator also comes with standard joystick remote control, it supports stable and safe operation.

Main Features

- $1.\,25\,\mathsf{Tons}\,/\,55,\!600\,\mathsf{lbs}.\,\mathsf{Planetary}\,\mathsf{Winch},2\,\mathsf{Pcs},\mathsf{Total}\,50\,\mathsf{Tons}\,/\,111,\!000\,\mathsf{lbs}.\,\mathsf{Optional}\,\mathsf{Multi}\,\mathsf{Drag}\,\mathsf{and}\,\mathsf{Turret}\,\mathsf{Winches}.$
- 2. 28 Tons / 62,000 lbs. Underlift Capacity, Tow Rate At Least 56 Tons / 125,000 lbs. Underlift Boom 3 Stages.
- 3. Continuous Boom Rotation, Recovery Boom 3 Stage
- 4. Joystick Remote Control
- 5. Optional Aluminum Tool Boxes

Specs

		/recker Specs	D : "	for a
No.		Content	Details	Unit
1	Name	50 Tons Rotator Wrecker		A 1 1717
2		2×25 Tons Main Winches		Additional winches are optional
3	Underlift	Underlift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 3 stage	
5	Legs	Hydraulic	Hydraulic rear and front supporting legs	
3	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control.	Optional Joystick type, chest mount, English display, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump	Double Pump	
		Hydraulic Cylinder		
		Hose		
		Valves	Italy	
		Connector		
11	Attachment s	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	İ
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting, other normal painting	All subframe, boom and under lift electrophoresis painting optional, extra USD2,000
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Spec	ifications			
1	Underlift	Retracted Lifting Capacity	28000	kg
		Retracted Length	1746	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3410	mm
		Undelift Tilt	-10	0
2	Boom	Retracted Lifting Capacity (45°)	50	ton
		Extended Lifting Capacity (45°)	11.5	ton
		Max. Lifting Tilt	62	0

		Max. Lifting Height	13129	mm
		Boom Hook(Max. Lifting Height)Away from Underlift(Folding)	5219	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	25	ton
		Туре	Planetary	
		Steel Wire Length	55	m
		Steel Wire Diameter	26	mm





Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881





ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN