

35600lb 16 Ton Medium Duty Wrecker Integrated Tow Truck With Front Outrigger

Our Product Introduction

for more products please visit us on hbitruck.com

Basic Information

- Place of Origin: Hubei, China
- Brand Name: iTruck
- Minimum Order Quantity: 1
- Price: \$22,000.00/units
- Packaging Details: Nude, covered with film protection
- Delivery Time: 60 days
- Supply Ability: 5 sets per month



Product Specification

- Product Name: Integrated Wrecker Truck Body
- Transmission Type: Manual
- Dimensions (L X W X H) (mm): Customs Made
- Condition: New
- WheelBase: As Required
- Subframe: Equipped
- Main Winch: 10 Tons, 2 Pcs
- Underlift: 3 Sections
- Underlift Tow Rating: 24 Tons
- Operation: Both Sides Manual
- Remote Control: Optional
- Warranty: 2 Year
- Highlight: 35600lb Medium Duty Wrecker,
35600lb Integrated Tow Truck,
16 Ton Medium Duty Wrecker



More Images



Product Description

16 TONS 18 TONS MEDIUM DUTY INTEGRATED WRECKER WITH FRONT OUTRIGGER AND SIDE PULLER

Product Description

The medium duty integrated series have different capacities from 8 tons to 18 tons.

ENGINEERED FOR STRENGTH AND DURABILITY

The 16 ton Integrated Medium Duty wrecker with a 35,600 lb. rated underlift and a modern, steel body that is maximized for available storage and deck space.

Main Features

1. 10 Tons / 22,200 lbs. Planetary Winch, 2 Pcs. Total 20 Tons / 44,500 lbs.
2. 12 Tons / 26,700 lbs. Underlift Capacity, Tow Rate At Least 24 Tons / 53,300 lbs.
3. Spacious Tool Compartments
4. Multi-Positional Rear Jacks
5. Optional Remote Control
6. Available Low Profile Tow Bar

Specs

16 Tons Wrecker Body Specs				
No.	Item	Content	Details	Unit
1	Name	16 Tons Wrecker Body		
2	Winches	2×10 Tons Main Winches		Side puller (10 tons) is optional, extra USD2,500
3	Underlift	Underlift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 2 stage, hexagon	
5	Legs	Rear	Hydraulic rear supporting legs	Front support legs are optional. Extra USD3,000
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD4,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Standard button remote control.	Optional Joystick type remote control, English Display Extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves	Italy Hydrocontrol	
		Cylinders		
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting	Subframe with boom and underlift EP painting extra USD1,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Specifications				
1	Underlift	Retracted Lifting Capacity	12000	kg
		Retracted Length	1505	mm
		Extended Lifting Capacity	4200	kg
		Extended Length	2760	mm
		Undelift Tilt	-10	°
		Towing Capacity	24-36	ton
2	Boom	Retracted Lifting Capacity (45°)	18	ton

		Extended Lifting Capacity (45°)	6.3	ton
3	Main Winches	Quantity	2	pcs
		Pulling Power	10	ton
		Type	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	18	mm



ITRUCK
SPECIAL VEHICLES

Hubei iTruck Import and Export Trading Co., Ltd

☎ 0086 19947597881

✉ alex@hbitruck.com

🌐 hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,
QINGSHAN DISTRICT, WUHAN