

16 Tons Planetary Winches Low Profile Wrecker Tow Bar Integrated Underlift

Our Product Introduction

for more products please visit us on hbitruck.com

Basic Information

- Place of Origin: Hubei, China
- Brand Name: iTruck
- Minimum Order Quantity: 1
- Price: \$16,500.00/units
- Packaging Details: Nude, covered with film protection
- Delivery Time: 60 days
- Supply Ability: 5 sets per month




Product Specification

- Product Name: Integrated Wrecker Truck Body
- Transmission Type: Manual
- Dimensions (L X W X H) (mm): Customs Made
- Condition: New
- WheelBase: As Required
- Subframe: Equipped
- Main Winch: 8 Tons, 2 Pcs
- Underlift: 3 Sections
- Underlift Tow Rating: 20 Ton
- Operation: Both Sides Manual
- Remote Control: Optional
- Warranty: 2 Year
- Highlight: Low Profile Wrecker Tow Bar, 16 Tons Wrecker Tow Bar, 16 Tons wrecker underlift



More Images



Our Product

Product Description

12 TONS 16 TONS PLANETARY WINCHES LOW PROFILE TOW BAR INTEGRATED UNDERLIFT

Product Description

The medium duty integrated series have different capacities from 8 tons to 16 tons.

ENGINEERED FOR STRENGTH AND DURABILITY

The 12 ton Integrated Medium Duty wrecker with a 22,200 lb. rated underlift and a modern, steel body that is maximized for available storage and deck space.

Main Features

1. 8 Tons / 17,800 lbs. Planetary Winch, 2 Pcs. Total 16 Tons / 35,600 lbs.
2. 10 Tons / 22,200 lbs. Underlift Capacity, Tow Rate At Least 20 Tons / 44,500 lbs.
3. Spacious Tool Compartments
4. Multi-Positional Rear Jacks
5. Optional Remote Control
6. Available Low Profile Tow Bar

Specs

12 Tons Wrecker Body Specs				
No.	Item	Content	Details	Unit
1	Name	12 Tons Wrecker Body		
2	Winches	2x8 Tons Main Winches		Side puller (8 tons) is optional, extra USD2,000
3	Underlift	Underlift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 2 stage, hexagon	
5	Legs	Rear	Hydraulic rear supporting legs	Front support legs are optional. Extra USD1,500
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD3,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Optional button remote control. Extra USD1,000	Optional Joystick type remote control, English Display Extra USD3,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves	Italy Hydrocontrol	
		Cylinders		
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Normal primer and surface painting	Subframe with boom and underlift EP painting extra USD1,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Specifications				
1	Underlift	Retracted Lifting Capacity	10000	kg
		Retracted Length	1505	mm
		Extended Lifting Capacity	3800	kg
		Extended Length	2760	mm
		Undelift Tilt	-10	°
		Towing Capacity	20-30	ton
2	Boom	Retracted Lifting Capacity (45°)	16	ton
		Extended Lifting Capacity (45°)	6	ton
3	Main Winches	Quantity	2	pcs
		Pulling Power	8	ton
		Type	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	18	mm





Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881



alex@hbitruck.com



hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,
QINGSHAN DISTRICT, WUHAN