30 Tons 360 Full Rotator Rotary Towing Truck Body Wrecker Body Custom Made

Basic Information

Place of Origin: Hubei, China
Brand Name: iTruck
Minimum Order Quantity: 1

• Price: \$51000/units

• Packaging Details: Nude, covered with protection film

Delivery Time: 75 daysSupply Ability: 5 unit/month



Product Specification

Product Name: Rotator

Dimensions (L X W X H)
 Custom Made To Fit Your Truck

(mm):

• Condition: New

• Drive Type: 6*4 Driving/8x4 Driving

WheelBase: As Required
Main Winch: 15 Tons, 2 Pcs
Auxiliary Winch: Optional
Underlift: G70, 3 Sections

Boom: G70, 3 Sections
 Remote Control: Wireless
 Hydraulic: DOT Certified

• Warranty: 3 Year

• Highlight: towing truck body Custom Made,

30 Tons towing truck body, Wrecker Body Custom Made



More Images







Product Description

30 TONS 360 FULL ROTATOR ROTARY TOWING WRECKER BODY Product Description

The rotator series has different capacities from 20 tons to 100 tons.

MAXIMUM STABILITY FOR MAXIMUM PERFORMANCE.

The strength and stability of the 30 tons rotator comes from the industry-leading scissor-style outriggers and unique frame design. The rotator also comes with standard joystick remote control, it supports stable and safe operation.

Main Features

- 1. 15 Tons / 33,300 lbs. Planetary Winch, 2 Pcs, Total 30 Tons / 66,600 lbs. Optional Multi Drag and Turret Winches.
- 2. 20 Tons / 44,500 lbs. Underlift Capacity, Tow Rate At Least 40 Tons / 88,800 lbs. Underlift Boom 3 Stages.
- 3. Continuous Boom Rotation, Recovery Boom 3 Stage
- 4. Joystick Remote Control
- 5. Optional Aluminum Tool Boxes

Specs

30 Tc	ons Rotator W	recker Specs		
No.	Item	Content	Details	Unit
1	Name	30 Tons Rotator Wrecker	Dotano	Offic
<u>. </u>	Winches	2×15 Tons Main Winches		Additional winches are optional
3	Under lift	Under lift	G70 material, 3 stage	раго органия
4	Boom	Boom	G70 material, 3 stage	
5	Legs	Hydraulic	Hydraulic rear and front supporting legs	
6	Frame	LED Lights Frame, full size	jospporting roge	
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control	Joystick type ches mount, English Display, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump	Double pump	
		Hydraulic Hose		
		Hose Connector		
		Valves	Italy	
		Cylinders		
11	Attachment s	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting, other normal painting	All subframe with boom and under lift EP painting optional, extra USD1,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Spec	ifications			
1	Underlift	Retracted Lifting Capacity	20000	kg
		Retracted Length	1746	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3492	mm
	1	Undelift Tilt	-10	0
	1	Towing Capacity	40	ton
2	Boom	Retracted Lifting Capacity (45°)	30	ton
		Extended Lifting Capacity (45°)	9	ton
		Max. Lifting Tilt	65	0

		Max. Lifting Height	11529	mm
		Boom Hook(Max. Lifting Height)Away from Underlift(Folding)	5219	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	15	ton
		Туре	Planetary	
		Steel Wire Length	60	m
		Steel Wire Diameter	18	mm





Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881





ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN