25 Ton Wrecker Body Integrated Underlift Boom Recovery Truck Body 44500 Lb.

Basic Information

Place of Origin: Hubei, China
Brand Name: iTruck
Minimum Order Quantity: 1

• Price: \$26,500.00/units

• Packaging Details: Nude, covered with film protection

Delivery Time: 60 days

• Supply Ability: 5 sets per month



Product Specification

Product Name: Integrated Wrecker Truck Body

• Transmission Type: Manual

• Dimensions (L X W X H) Customs Made

(mm):

• Condition: New

WheelBase: As Required
Subframe: Equipped
Main Winch: 10 Tons, 2 Pcs

• Underlift: 3 Sections, Optional 4

• Underlift Tow Rating: 25 Ton

• Operation: Both Sides Manual

Remote Control: OptionalWarranty: 2 Year

• Highlight: Recovery Truck Body 44500 Lb.,

25 Ton Wrecker Body, Wrecker Body 44500 Lb.



More Images





Product Description

25 TONS INTEGRATED RECOVERY UNDERLIFT BOOM TRUCK BODY

Product Description

The heavy duty integrated series have different capacities from 20 tons to 50 tons.

BUILT FOR STRENGTH, RELIABILITY AND DURABILITY

The 25 tons integrated wrecker features a 44,500 lb. 2- or 3-stage wrecker boom, corrosion, resistant body and optional 3- or 4-stage underlifts – all designed with strength and performance in mind.


Main Features

- 1. 10 Tons / 22,200 lbs. Planetary Winch, 2 Pcs. Total 20 Tons / 44,500 lbs.
- 2. 25 Tons / 55,500 lbs. Underlift Capacity, Tow Rate At Least 50 Tons / 111,000 lbs.
- 3. Optional Remote Control
- 4. Sides Tool Boxes
- 5. Optional Front Legs and Side Pullers

Specs

25 To	ons Wrecker I	Body Specs		
Vo.	Item	Content	Details	Unit
1	Name	25 Tons Wrecker Body		
2	Winches	2×10 Tons Main Winches	Side puller/ extra winch is optional, extra USD2,500	
3	Under lift	Under lift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 2 stage, hexagon	
5	Legs	Rear	Hydraulic rear supporting legs	Front supporting legs are extra USD3,500 or front outrigger extra USD5,000.
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control	Joystick type remote control, English Display, optional, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves		
		Cylinders		
11	Attachment s	5 Sets of Forks	4 sets for axle, 1 set for suspension	
	1	U shape tyres holder	1 set	
	1	Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Primer and surface painting	All subframe with boom, under lift and tool box EP painting optional, extra USD2,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
		Packaging	Boxes and under lift protected for the painting	
Spec	ifications			
1	Underlift	Retracted Lifting Capacity	25000	kg

		Retracted Length	1746	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3110	mm
		Undelift Tilt	-10	0
		Towing Capacity	50	ton
2	Boom	Retracted Lifting Capacity (45°)	20	ton
		Extended Lifting Capacity (45°)	12	ton
		Max. Lifting Tilt	33	0
		Max. Lifting Height	7022	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	10	ton
		Туре	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	18	mm



Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881



alex@hbitruck.com



hbitruck.com

ROOM 8, 17TH FLOOR, BUILDING A, JIANGWAN INTERNATIONAL 2ND PHASE, GUTIAN ROAD NO. 19, QIAOKOU DISTRICT, WUHAN CITY, HUBEI PROVINCE