Factory Direct Sale 5 cbm Cleaning Water tank and 5 cbm High Pressure Road Sweeper Truck Street Sweeping Machine

Basic Information

Place of Origin: Hubei, China
Brand Name: itruck
Certification: ccc
Minimum Order Quantity: 1

Price: \$43,700.00/units 1-4 units
Packaging Details: nude with waxing
Delivery Time: 20-25 working days
Payment Terms: L/C, T/T, D/P
Supply Ability: 50 units per month



Product Specification

Condition: New
Transmission Type: Manual
Emission Standard: EURO 3
Fuel Type: Diesel

Dimensions (L X W X H) 7000X2300X2700 Mm

(mm)

Gross Vehicle Weight: 1100

• After-sales Service Video Technical Support, Field Installation, Provided: Commissioning And Training, Free Spare

Parts

Product Name: Road Sweeper Truck

• Driving Type: 4*2

Keyword: Street Clean Truck
Engine Power: 120hp To 140hp
Brand: Dongfeng

Highlight: Street Sweeping Machine Sweeper Truck



More Images











Product Description

Factory Direct Sale 5 cbm Cleaning Water tank and 5 cbm High Pressure Road Sweeper Truck Street Sweeping Machine

High pressure washing and sweeping truck.

1. Working principle of washing and sweeping truck

The cleaning and sweeping vehicle combines the functions of a road sweeper and a high-pressure cleaning vehicle. Generally, it comes standard with two center mounted brushes (equipped with a V-shaped high-pressure water spray rod in front of the brushes) and a center mounted suction nozzle (with a built-in high-pressure water spray rod). The washing and sweeping vehicle sprays high-pressure water from the high-pressure water spray rod during operation, which can flush stubborn attachments on the road surface. The water and garbage are sucked into the garbage bin together with the suction nozzle. Due to the high water consumption of the washing and sweeping vehicles during the operation, the water tank is relatively large. Therefore, the washing and sweeping vehicles are all modified from chassis with a wheelbase of 3800 mm or more. The washing and sweeping vehicle is equipped with a 17 meter high-pressure water flushing reel and a high-pressure water gun, making it more convenient and efficient to clean roads, sidewalks, and small advertisements.

2. Applicable environment for washing and sweeping truck

The cleaning truck has good cleaning effect and convenient maintenance, and is suitable for mechanized cleaning, sweeping, spray dust reduction and other cleaning operations of urban roads, highways, squares, airports, docks, tunnels, bridges, separation walls, curbs and curb facades.

Main Technical specifications

Overview

Chassis model	EQ1110SJ8BDC	
Wheelbase	3800mm	
Front/rear suspension	1130/2070 mm	
Chassis engine	YC4FA120-30	
Chassis engine	88kw, 2982cc, 120hp	
Spare engine	64 kW	
Max upgrade angle	30%	
Emission standard	Eu 3	
Accelerating outside noise	≤84dB(A)	
Max speed	100 km/h	
Approach angle	20°	
Departure angle	11°	
Kurb weight	7045 kg	
Whole weight	11450kg	
Whole dimension	7000×2200×2700mm	
Minimum height above ground	250 mm	
High pressure clean	•	
Clean speed	3~20 Km/h	
Clean width	3 m	
Water pressure	12 MPa	
Water pump flow	115 L/min	
Clean and suction performance		
Cleaning efficiency	≥95%	
Maximum suction particle size	110 mm	
Clean and suction width	3 m	
Max clean capacity	60000 m ² /h	
Disc brush size	≥400 mm	
Clean and suction speed	3-20 km/h	
Tank capacity	•	
Water tank volume	5 m ³	
Dust tank volume	5 m ³	
Dump bin tilting angle	≥46°	
Discharge door opening angle	≥85°	
Hydraulic Hydraulic system		
Model	Open, electrical control	

Water spray system	nozzles, etc.
Water enroy eyetem	Electric diaphragm pumps, water filters,
Water filter	Mesh type
Spray nozzles model	High pressure washing type
Water valve pressure	7 MPa
Water valve model	Hydraulic pressure ball valve.
Speed	1150 r/min
System pressure	10 MPa
No:.	Germany PT36
Model	post pump
High pressure water system	
Suction plate width	1800mm
Suction plate diameter	180 mm
Model	Double suction, hydraulic control, spring suspension.
Sucking plate	
Brush angle	Tilt forward: 4-6 degrees Tilt: 4-7 degrees
brusri diameter	
Model Brush diameter	controlled independently, with a evasive reply function. 850 mm
	Center two swabs, driven by a hydraulic motor, and the front right can be
Sweeping devise	
Battery	24 V
Voltage	24 V
Model	DC24 V
Electrical system	·
Oil temperature	60 °C
Oil tank	60 L
System pressure	16 MPa
Major parts	cylinder, solenoid valve
	Gear pump, hydraulic motor, hydraulic

Truck tools

No:.	ITEM	QTY	REMARK
1	Fire hose	2	
2	Fire wrench	1	
3	Water filter wrench	1	
4	High pressure water jet gun	1	
5	Spare tire	1	7.00R16
6	Manual hydraulic pump rocker	1	

Truck spare parts

No:.	ITEM	QTY	
1	Brushing	1	
2	Suction cup front rubber	1	
3	After the suction cup	1	
4	Fan belt	5	
5	Water pump belt	3	
6	Casters	4	
7	O-rings and combination washers		
8	Middle baffle rubber	1	
9	Seal	1	

Major import configurations

No.	Item	Туре	Manufacturer
1	High pressure water pump	PT36	Germany PINFL
2	Automatic unloading after valve	VB200/150	Germany PINFL
3	Flood valve	VS200-180	Germany PINFL

4	Nozzle	B1/4MEG	America spray
Ľ			company
5	Liquid level switch	LME200B5/24V	Italy SOFIMA
6	CPU	6ES7 214-1AD23- OXB0	Germany SIEMENS
7	Digital quantity extension module	6ES7 223-1PH22- OXA0	Germany SIEMENS
8	The central distribution box	DVEC	America COOPER
9	Stepping motor	57H41-2.7-001	America Haydn
10	Switch gear cabinet	NE-AG	Korea HIBOX
11	Switch Control		Japan IDEC
12	Proximity switch	NBB10-30GM50-E0	PEPPRL FUCHS
13	Suction pipe		NORRES
14	Hydraulic motor	BMR125	Brevini
15	Hydraulic valve	SWH-G02-C4-D2H	Radix stemonae machines

High pressure road sweeper truck picture













High pressure road sweeper truck function display













High pressure road sweeper truck bulk order













High pressure road sweeper truck loading











