

## 40 Tons Boom Capacity Heavy Duty Wrecker Body Rotator Remote Control

Our Product Introduction

for more products please visit us on [hbitruck.com](http://hbitruck.com)

### Basic Information

- Place of Origin: Hubei, China
- Brand Name: iTruck
- Minimum Order Quantity: 1
- Price: \$61000/units
- Packaging Details: Nude, covered with protection film
- Delivery Time: 75 days
- Supply Ability: 5 unit/month



### Product Specification

- Product Name: Rotator
- Dimensions (L X W X H) (mm): Custom Made To Fit Your Truck
- Condition: New
- Drive Type: 8\*6 Driving/10x6 Driving
- WheelBase: As Required
- Main Winch: 20 Tons, 2 Pcs
- Auxiliary Winch: Optional
- Underlift: G70, 3 Sections
- Boom: G70, 3 Sections
- Remote Control: Wireless
- Hydraulic: DOT Certified
- Warranty: 3 Year
- Highlight: 40 Tons Heavy Duty Wrecker Body,  
40 Tons tow truck wrecker body,  
Remote Control Heavy Duty Wrecker Body



### More Images



### Product Description

#### 40 TONS BOOM CAPACITY HEAVY DUTY WRECKER BODY ROTATOR

##### Product Description

The rotator series has different capacities from 20 tons to 100 tons.

MAXIMUM STABILITY FOR MAXIMUM PERFORMANCE.

The strength and stability of the 40 tons rotator comes from the industry-leading scissor-style outriggers and unique frame design. The rotator also comes with standard joystick remote control, it supports stable and safe operation.

Our Product

### Main Features

1. 20 Tons / 44,500 lbs. Planetary Winch, 2 Pcs, Total 40 Tons / 88,800 lbs. Optional Multi Drag and Turret Winches.
2. 25 Tons / 55,500 lbs. Underlift Capacity, Tow Rate At Least 50 Tons / 111,000 lbs. Underlift Boom 3 Stages.
3. Continuous Boom Rotation, Recovery Boom 3 Stage
4. Joystick Remote Control
5. Optional Aluminum Tool Boxes

### Specs

40 Tons Rotator Wrecker Specs				
No.	Item	Content	Details	Unit
1	Name	40 Tons Rotator Wrecker		
2	Winches	2x20 Tons Main Winches		Additional winches are optional
3	Underlift	Underlift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 3 stage	
5	Legs	Hydraulic	Hydraulic rear and front supporting legs	
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control.	Optional Joystick type, chest mount, English display, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump	Double Pump	
		Hydraulic Cylinder		
		Hose		
		Valves	Italy	
		Connector		
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting, other normal painting	All subframe, boom and under lift electrophoresis painting optional, extra USD2,000
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Specifications				
1	Underlift	Retracted Lifting Capacity	25000	kg
		Retracted Length	1660	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3110	mm
		Undelift Tilt	-10	°
2	Boom	Retracted Lifting Capacity (45°)	40	ton
		Extended Lifting Capacity (45°)	9.2	ton
		Max. Lifting Tilt	62	°
		Max. Lifting Height	13129	mm
		Boom Hook(Max. Lifting Height)Away from Underlift(Folding)	5219	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	20	ton
		Type	Planetary	
		Steel Wire Length	55	m
		Steel Wire Diameter	26	mm





**Hubei iTruck Import and Export Trading Co., Ltd**



0086 19947597881



alex@hbitruck.com



hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,  
QINGSHAN DISTRICT, WUHAN