

# Dongfeng 10m3 Tank Road Washing Truck Safe And Hygienic Vehicle

Western Union

0
Ĩ
Τ
2
×
č
0
二.
ntr
0
Ъ.
5
달.

9

for more products please visit us on hbitruck.com

Basic Information	
<ul> <li>Place of Origin:</li> </ul>	Hubei
<ul> <li>Brand Name:</li> </ul>	Dongfeng
Certification:	ccc
Minimum Order Quantity:	1
Price:	43200
<ul> <li>Packaging Details:</li> </ul>	nude with waxing
<ul> <li>Delivery Time:</li> </ul>	30-35 working days
<ul> <li>Payment Terms:</li> </ul>	L/C, D/A, D/P, T/T,
<ul> <li>Supply Ability:</li> </ul>	50 units per month

## **Product Specification**

<ul> <li>Tank Capacity:</li> </ul>	10 Cubic Meters

- Dust Suppression System: Yes
- Power Source: Diesel
- Operating Weight: 7 Tons
- Sweeping Width:
- 10-15 Meters 5-15 Km/h Cleaning Speed:
- Type: Mechanical
- Curb Climbing Ability: 30 Cm
- Cleaning Spray Rack Width: 2.3-3.5 M
- Spray Rack Deflection 30 ° Angle:
- Clean Water Rated Flow: ≥ 150 L/min
- Spray Flow: ≥ 125 L/min
- Rated Of Pressure Washing10 Mpa Water:

I am Drasser Class Flam. 500 000 I /min



## More Images



### Product Description

#### High pressure road washing truck.

1. Working principle of road washing truck

Equipped with a front spray rack, By compressing water molecules into small water droplets under high pressure, fast and efficient cleaning and cleaning effects can be achieved. This type of vehicle is usually used to remove dirt, grease, mud, and other stains from the surface of road.

2. Applicable environment for road washing truck

In some industrial settings, such as factories, warehouses, etc., high-pressure cleaning vehicles can be used to remove harmful substances from the air to improve the air quality of the working environment. In addition to road cleaning, they are also widely used in building cleaning and other cleaning fields. In terms of vehicle cleaning, high-pressure cleaning vehicles can penetrate into the hidden corners of the vehicle, thoroughly remove various dirt and stubborn oil stains, and also have the effect of sterilization and disinfection, effectively ensuring the safety and hygiene of vehicle use

#### Main Technical specification

Dongfeng high pressure c	leaning truck
0 0 0 1	
Overall dimensions	8980×2500×3080 mm
Tank dimention	5400x2280x1380 mm
Tank volume	10 m3
GVW	18000 kg
Curb weight	7960 kg
Payload	10000 kg

for more products please visit us on hbitruck.com

4500 mm
1880/1800 mm
1430/2160 mm
23/12 °
80 km/h
5000/10000 kg
10.00R20
2
Power
8JS85TE-C
3
24V
·
Dongfeng Cummins
B190-33
5900ml/140Kw, 190Hp
2500RPM
640Nm at 1500rpm
Diesel, 6 direct-line, turbocharge and
water cooling
102mm
120 mm
JX493G3, 2771cc/57kw/3600r/min
2.3-3.5 m
30 °
5-15 Km/h
ter 10 Mpa
≥ 150 L/min
≥ 125 L/min
2 125 E/IIIII
≥ 16 m
500-900 L/min
≥ 35 m
≥ 6 m
2 6 11
80 Km/h
30 °
10 m
19 m
SACHS
¢430mm
Hydraulic control with air booster, pulling
pulling
DTO with good nump
PTO with gear pump
850Nm
aning device(1 set)
e sets)
zzle(2 set)
gun(1 set)
e nozzle(2 set)
arinklar(2 cat)
prinkler(2 set) sprinkler(2 set)

High pressure road washing truck picture



High pressure road washing truck function display









High pressure road sweeper truck loading



S 0086 19947597881 C alex@hbitruck.com ihitruck.com ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN