Chinese Dongfeng Truck Mounted Road Sweeping Machine 6x4 20cbm

Basic Information

- Place of Origin:
- Brand Name:
- Certification: CCC

Hubei

1

Dongfeng

- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- 43200 nude with waxing 30-35 working days L/C, D/A, D/P, T/T, Western Union 50 units per month



Product Specification

- Tank Capacity: 20 Cubic Meters • Dust Suppression System: Yes • Power Source: Diesel • Operating Weight: 15 Tons · Sweeping Width: 10-15 Meters Cleaning Speed: 5-15 Km/h Mechanical • Type: • Curb Climbing Ability: 30 Cm • Cleaning Spray Rack Width:2.3-3.5 M
 - 30 ° Spray Rack Deflection Angle:
 - Clean Water Rated Flow: ≥ 150 L/min
 - Spray Flow: ≥ 125 L/min
 - Rated Of Pressure Washing10 Mpa Water:



More Images





500 000 L /m





20 CBM 6X4 High Pressure Cleaning Truck for Effective Cleaning of Hidden Corners of Vehicles

1. Working principle of road washing truck

Equipped with a front spray rack, By compressing water molecules into small water droplets under high pressure, fast and efficient cleaning and cleaning effects can be achieved. This type of vehicle is usually used to remove dirt, grease, mud, and other stains from the surface of road.

2. Applicable environment for road washing truck

In some industrial settings, such as factories, warehouses, etc., high-pressure cleaning vehicles can be used to remove harmful substances from the air to improve the air quality of the working environment. In addition to road cleaning, they are also widely used in building cleaning and other cleaning fields. In terms of vehicle cleaning, high-pressure cleaning vehicles can penetrate into the hidden corners of the vehicle, thoroughly remove various dirt and stubborn oil stains, and also have the effect of sterilization and disinfection, effectively ensuring the safety and hygiene of vehicle use

Main Technical specification	
Dongfeng high pressure cleaning truck	
Overall dimensions	9800×2500×3080 mm
Tank dimention	6800x2280x1380 mm
Tank volume	20 m3
GVW	25000 kg
Curb weight	12500 kg
Payload	14150 kg
Wheel base	4350+1300 mm
F/R track base	1880/1800 mm
F/R suspension	1430/2160 mm
Approach/departure angle	23/12 °
Max speed	80 km/h
Axle Load	5000/10000 /10000kg
Tire specification	315/80R22.5
Number of axles	3
Steering	Power
Transmission	9F&1R ZF9S1820
Cab passenger	3
Electric System	24V
Engine model	
Manufacturer	Dongfeng Cummins
Туре	L375 30
Emission/kw	8900ml/276Kw, 375Hp
Rated power speed	2200RPM
Maximum torque	1480Nm at 1400rpm
· · · · · · · · · · · · · · · · · · ·	Diesel, 6 direct-line, turbocharge and
type	water cooling
Cylinder bore	114mm
Stroke	145 mm
Secondary engine model	JX493G3, 2771cc/57kw/3600r/min
High pressure clean	
Cleaning spray rack width	2.3-3.5 m
Spray rack deflection angle	30 °
Sweeping speed	5-15 Km/h
Rated of pressure washing water	
Clean water rated flow	≥ 150 L/min
Spray flow	≥ 125 L/min
Low pressure clean	
Clean width	≥ 16 m
Clean water flow	500-900 L/min
Water gun range	≥ 35 m
Self-priming height	≥6 m
Driving performance	- • …
Max speed	80 Km/h
Maximum grade	30 °
Braking length	10 m
Minimum turning diameter	19 m
Clutch	, , , , , , , , , , , , , , , , , , ,
Type SACHS	
Plate's diameter	¢430mm
	۳۰۰۰۰۰۱۱۱۱

Main Technical specification

Operating system	Hydraulic control with air booster, pulling	
РТО	·	
Туре	PTO with gear pump	
Maximum output torque	850Nm	
Standard configuration	·	
1, Front high pressure road cleaning device(1 set)		
2, Front high pressure nozzle(2 sets)		
3, Front low pressure spray nozzle(2 set)		
4, Middle upper high pressure gun(1 set)		
5, Milddle bottom high pressure nozzle(2 set)		
6, Rear low pressure shower sprinkler(2 set)		
7, Rear high pressure annular sprinkler(2 set)		
8, Rear high pressure gun(1 set)		

High pressure road washing truck picture



High pressure road washing truck function display



High pressure road sweeper truck bulk order



High pressure road sweeper truck loading

