

Heavy Duty Road Washing Truck With 20M3 Tank Volume And 25000KG GVW

Our Product Introduction

for more products please visit us on hbitruck.com

Basic Information	
 Place of Origin: Brand Name: Certification: 	Hubei Dongfeng ccc
Minimum Order Quantity:Price:	1 43200
 Packaging Details: Delivery Time: 	nude with waxing 30-35 working days
Payment Terms:Supply Ability:	L/C, D/A, D/P, T/T, Western Union 50 units per month



Product Specification

 Tank Capacity: 	20 Cubic Meters
	 Tank Capacity:

- Dust Suppression System: Yes
- Power Source: Diesel
- Operating Weight: 15 Tons 10-15 Meters
- Sweeping Width:
- 5-15 Km/h Cleaning Speed:
- Type: Mechanical
- Curb Climbing Ability: 30 Cm
- Cleaning Spray Rack Width: 2.3-3.5 M
- Spray Rack Deflection 30 ° Anale:
- Clean Water Rated Flow: ≥ 150 L/min
- Spray Flow: ≥ 125 L/min
- Rated Of Pressure Washing10 Mpa Water:

I am Drasser Class Flam. 500 000 I /min



More Images



Product Description

20 M3 Tank Volume and 25000 KG GVW for Heavy Duty Cleaning with Road Washing Truck

1. Working principle of road washing truck

Equipped with a front spray rack, By compressing water molecules into small water droplets under high pressure, fast and efficient cleaning and cleaning effects can be achieved. This type of vehicle is usually used to remove dirt, grease, mud, and other stains from the surface of road.

2. Applicable environment for road washing truck

In some industrial settings, such as factories, warehouses, etc., high-pressure cleaning vehicles can be used to remove harmful substances from the air to improve the air quality of the working environment. In addition to road cleaning, they are also widely used in building cleaning and other cleaning fields. In terms of vehicle cleaning, high-pressure cleaning vehicles can penetrate into the hidden corners of the vehicle, thoroughly remove various dirt and stubborn oil stains, and also have the effect of sterilization and disinfection, effectively ensuring the safety and hygiene of vehicle use

Main Technical specification

Dongfeng high pressure cleaning truck	
Overall dimensions	9800×2500×3080 mm
Tank dimention	6800x2280x1380 mm
Tank volume	20 m3
GVW	25000 kg
Curb weight	12500 kg

Our Product Introduction

for more products please visit us on hbitruck.com

Payload	14150 kg
Wheel base	4350+1300 mm
F/R track base	1880/1800 mm
F/R suspension	1430/2160 mm
Approach/departure angle	23/12 °
Max speed	80 km/h
Axle Load	5000/10000 /10000kg
Tire specification	315/80R22.5
Number of axles	3
Steering	Power
Transmission	9F&1R ZF9S1820
Cab passenger	3
Electric System	24V
Engine model	•
Manufacturer	Dongfeng Cummins
Туре	L375 30
Emission/kw	8900ml/276Kw, 375Hp
Rated power speed	2200RPM
Maximum torque	1480Nm at 1400rpm
	Diesel, 6 direct-line, turbocharge and
type	water cooling
Cylinder bore	114mm
Stroke	145 mm
Secondary engine model	JX493G3, 2771cc/57kw/3600r/min
High pressure clean	1
Cleaning spray rack width	2.3-3.5 m
Spray rack deflection angle	30 °
Sweeping speed	5-15 Km/h
Rated of pressure washing water	10 Mpa
Clean water rated flow	≥ 150 L/min
Spray flow	≥ 125 L/min
Low pressure clean	
Clean width	≥ 16 m
Clean water flow	500-900 L/min
Water gun range	≥ 35 m
Self-priming height	≥6 m
Driving performance	1
Max speed	80 Km/h
Maximum grade	30 °
Braking length	10 m
Minimum turning diameter	19 m
Clutch	1
Туре	SACHS
Plate's diameter	¢430mm
	Hydraulic control with air booster,
Operating system	pulling
PTO	·
Туре	PTO with gear pump
Maximum output torque	850Nm
Standard configuration	
1, Front high pressure road clear	
2, Front high pressure nozzle(2 s	
Front low pressure spray nozz	
	n(1 set)
4, Middle upper high pressure gu	
5, Milddle bottom high pressure r	
	nkler(2 set)

High pressure road washing truck picture















High pressure road washing truck function display















ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, OINGSHAN DISTRICT, WUHAN