Dongfeng Euro 3 RHD LHD Custom Flatbed Tow Truck 5980x2350x2600mm

Basic Information

Place of Origin: Hubei, ChinaBrand Name: Dongfeng

Minimum Order Quantity: 1Packaging Details: NudeDelivery Time: 15 days

• Supply Ability: 30 sets per month



Product Specification

Product Name: Flatbed Wrecker Truck
 Dimensions (L X W X H) 5980x2350x2600mm

(mm):
• Condition:

New

• Main Winch: 4 Tons

• Underlift: 2 Sections, 3 Tons

• Underlift Tow Rating: 6 Tons

Operation: Both Sides Manual

Remote Control: OptionalWarranty: 1 Year

• Bed Dimension: 5200x2300mm

• Highlight: LHD Custom Flatbed Tow Truck,

RHD Custom Flatbed Tow Truck, 2600mm Flatbed Tow Truck



More Images





Product Description

4 TONS DONGFENG EURO 3 RHD LHD TOW TRUCKS WRECKERS TILT TOW TRUCK

Product Description

The 4 tons Dongfeng flatbed wrecker truck is available in steel, with multiple deck length and width configurations and different structural deck capacity for more strength and durability on the job.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4.

Other special requirements you want.

Main Features

- 1. Bed Length 5.2 m. Capacity 4 Tons.
- 2. Optional Hitch Ball. Optional Remote Control.
- 3. Optional Material from Q235B, Q345, G70, NM500, Hardox 450 etc.

Truck Specs

3 Tons Dongfeng Tow Truck	
Overview	
Name	3 Tons Dongfeng Tow Truck
Overall Dimension(LxWxH)	5990x2300x2360(mm)
Total Mass	6050Kg
Rated Payload	3000Kg
Kerb Weight	3050Kg
Passenger	3
Approach/Departure Angle	19/15
The Parameters of Chassis	
Manufacture/Model	Dongfeng
Driving Type	4x2 RHD/LHD
Wheel Base	3300 mm
Gearbox	Six speed lever with five speed forward
Gealbox	and one reverse, manual
Front/Rear Track	1506/1466(mm)
Tyre	7.00R16
The Number of Tyre	6+1(spare tyre)
Front/Rear Suspension	1032/1658(mm)
Leaf Spring Number	8/9+5, 6/8+4
The Paremeters of Engine	·
Manufacturer/Model	ChaoChai
Rated Power	82hp
Fuel Type	Diesel oil
Displacement/Capacity	3856ml
Emission Standard	Euro3
Cylinder	Straight/4/intercooling
Max. torque	345N.m
Velocity	3200rpm

Body Specs

General Settings		Customizable, electrophoresis painting is optional and extra USD400
	Winch Capacity	4 tons
	Lift Capacity	4 tons
	Extension Capacity	4 tons
	Underlift Capacity	4 tons
	Platform Material	Q235B, 4mm thick
	Platform Type	Checkered
	Platform Dimension	5600 x 2300 mm (customizable)
	Wireless Remote Control	Optional
	Subframe with Underlift	Match to chassis
	Siren Long Lamp with Speaker	1 pcs
	Sides Lights	8 pcs
	Frame Lights with Lights Seat	6 pcs

Hydraulic System	Bed Extension Cylinder with Seat	1 pcs
	Bed Lift Cylinder with Seat	2 pcs
	Underlift lift Cylinder	2 pcs
	Underlift Extension Cylinder	1 pcs
	Hydraulic Winch	1 pcs
	Hydraulic Pump	1 pcs
	Hydraulic Multi Way Valve	1 pcs
	Hydraulic Balance Valve	2 pcs (1 for lift and 1 for underlift)
	Hydraulic Hose	1 set
	Hydraulic Hose Containment	1 set
	Hose Sleeve	1 pcs
	Manual Control with Stainless Steel Seat	2 sets (on both sides)
	Oil Tank	1 pcs
Accessories	Auxiliary Wheels	2 pcs
	Straps	4 pcs
	Toolbox	2 pcs
	Wheel Grids	2 pcs
	L arms	2 pcs
	Fence	2 pcs
	Mudflap	2 pcs
	Lamp Frame	1 pcs
	Tow Chain	1 pcs
	Frame and Lights Bolts	1 set
	Toolbox and Fence Brackets Square Tube	1 set





Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881





ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN