Dongfeng 120hp Flatbed Wrecker Truck 4 Tons Full Landing 0 Degree

Basic Information

Place of Origin: Hubei, ChinaBrand Name: Dongfeng

Minimum Order Quantity: 1Packaging Details: NudeDelivery Time: 15 days

• Supply Ability: 30 sets per month



Product Specification

Product Name:
 Full Landing Lay Flat Wrecker Truck

• Dimensions (L X W X H) 7600x2350x2600mm

(mm):

Condition: New Main Winch: 4 Tons

• Underlift: 2 Sections, 3 Tons

• Underlift Tow Rating: 6 Tons

Operation: Both Sides Manual

Remote Control: OptionalWarranty: 1 Year

• Bed Dimension: 5600x2350mm

• Highlight: Full Landing Flatbed Wrecker Truck,

120hp Flatbed Wrecker Truck, 120hp flatbed towing truck



More Images







Product Description

4 TONS DONGFENG 120HP FULL LANDING 0 DEGREE FLATBED WRECKER TOWING TRUCK

Product Description

The 4 tons Dongfeng flatbed wrecker truck is available in steel, with multiple deck length and width configurations and different structural deck capacity for more strength and durability on the job.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4.

Other special requirements you want.

Main Features

- 1. Bed Length 5.6 m. Capacity 4 Tons.
- 2. Optional Hitch Ball. Optional Remote Control.
- 3. Optional Material from Q235B, Q345, G70, NM500, Hardox 450 etc.

Truck Specs

4 Tons Lay Flat Bed Wrecker Overview			
Dimension (LxWxH)	7600x2350x2600(mm)		
Total Mass	10495 Kg		
Rated Payload	5000 Kg		
Kerb Weight	5495 Kg		
Passenger	3		
The Parameters of Chassis			
Manufacture/Model	Dongfeng		
Driving Type	4*2 left hand drive		
Wheel Base	3800 mm		
Gearbox	Five speed forward and one reverse, manual		
Front/Rear Track	1835/1640(mm)		
Tyre	7.50R16		
The Number of Tyre	6+1(spare tyre)		
Front/Rear Suspension	1180/1715(mm)		
Leaf Spring Number	11/9+7		
AC, Air Brake, Power Steer, Central Locking, Power Windows, etc.	Equipped		
The Parameters of Engine			
Manufacturer/Model	YuChai		
Rated Power	120hp		
Fuel Type	Diesel oil		
Displacement/Capacity	3856ml		
Emission Standard	Euro 3		
Cylinder	Straight/4/intercooling		
Max. torque	450N.m		
Velocity	2500rpm		

Body Specs

General Set	ttings Color	Customizable, electrophoresis painting is optional
	Winch Capacity	5 tons
	Lift Capacity	5 tons
	Extension Capacity	5 tons
	Underlift Capacity	3 tons (can tow up to 6 tons)
	Platform Material	Q235B, 4mm thick
	Platform Type	Checkered or smooth
	Platform Dimension	5000-7000 x 2500 mm, as required
	Wireless Remote Control	Optional, extra USD500
	Subframe with Underlift	Match to chassis
Lights	Siren Long Lamp with Speaker	1 pcs
	Sides Lights	8 pcs
	Frame Lights with Lights Seat	6 pcs

Hydraulic System	Bed Extension Cylinder with Seat	1 pcs
	Bed Lift Cylinder with Seat	2 pcs
	Underlift lift Cylinder	2 pcs
	Underlift Extension Cylinder	1 pcs
	Hydraulic Winch	1 pcs
	Hydraulic Pump	1 pcs
	Hydraulic Multi Way Valve	1 pcs
	Hydraulic Balance Valve	2 pcs (1 for lift and 1 for underlift)
	Hydraulic Hose	1 set
	Hydraulic Hose Containment	1 set
	Hose Sleeve	1 pcs
	Manual Control with Stainless Steel Seat	2 sets (on both sides)
	Oil Tank	1 pcs
Accessories	Trolleys	2 pcs
	Straps	4 pcs
	Toolbox	2 pcs
	Wheel Grids	2 pcs
	L arms	2 pcs
	Fence	2 pcs
	Mudflap	2 pcs
	Lamp Frame	1 pcs
	Bed Position Limit	1 set
	Frame and Lights Bolts	1 set
	Toolbox and Fence Brackets Square Tube	1 set



Hubei iTruck Import and Export Trading Co., Ltd







ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN