20Cbm Japanese ISUZU VC61 Sewer Suction Truck Sewage Tank Truck

Basic Information

Place of Origin: HubeiBrand Name: ISUZUCertification: ccc

Model Number: QL4250U4NDZ

Minimum Order Quantity: 1Price: 76200\$

Packaging Details: nude with waxing
Delivery Time: 30-35 working days
Payment Terms: T/T, D/P, L/C
Supply Ability: 50 units per month



Product Specification

Name: ISUZU High Pressure Sewage Clean And

Suction Truck

Water Tank: 8000 Liters
Sewage Tank: 12000 Liters
Total Amount: 25000 Kg
Driving Type: 6x4

Wheelbase: 4565+1370 MmGearbox: FAST 12

Tyre Model: 295/80R22.5 18PR
Engine Model: 6UZ1-TCG51
Rated Power: 257kw/350hp
Displacement/Capacity: 9839 MI
High Pressure Pump: Pinfu 330
Vacuum Suction Pump: SK-12

• Highlight: 20Cbm Sewer Suction Truck,



More Images











Product Description

20 cbm Japanese ISUZU VC61 Combine Sewage Clean and Suction Truck

The cleaning and suction truck has the functions of flushing, dredging, suction, and reverse discharge.

The function of a sewage suction truck:

The cleaning and suction truck is a new type of environmental sanitation vehicle used for collecting, transferring, and cleaning the transportation of sludge and sewage. It has the function of self suction and self discharge, and its advantages are fast working speed, large capacity, and convenient transportation. It is suitable for collecting and

transporting liquid substances such as feces, mud, crude oil, etc.

The working principle of cleaning the suction truck:

The working principle of cleaning and suction trucks is mainly based on the siphon principle. When the fecal suction hose is submerged under the liquid surface and air is sucked in, the pressure inside the tank will gradually decrease due to the inability to be replenished, causing the fecal liquid to enter the tank through the fecal suction hose under atmospheric pressure. In addition, when the siphon tube approaches the bottom of the tank, air is continuously discharged into the tank. As the air cannot be discharged, the pressure inside the tank will increase, and the feces will be discharged outside the tank through the siphon tube and suction hose under the action of compressed air.

Main Technical specification

Overview	
	20 cbm ISUZU High Pressure sewage
Name	Clean and Suction Truck
Dimension(LxWxH)	10100x2550x3950 mm
Total Mass	25000 kg
Rated Payload	7370 kg
Kerb Weight	17500 kg
Passenger	3
Approach/Departure Angle	17°/10 °
The Parameters of Chassis	17.710
Manufacture/Model	ISUZU VC61
Driving Type	6x4
Wheel Base	4565+1370 mm
Gearbox	FAST 12
Front/Rear Track	2060/1855 mm
Tyre model	295/80R22.5 18PR
The Number of Tyre	10+1 (spare tyre)
Front/Rear Suspension	1370/2710 mm
The Paremeters of Engine	10.0,2.10
Manufacturer/Model	6UZ1-TCG51
Rated Power	257kw/350hp
Fuel Type	Diesel oil
Displacement/Capacity	9839 ml
Emission Standard	Eu 5
Cylinder	6
Max. Torque/ speed	1422 N.m/ 1400rpm
Velocity	2000 rpm
The Parameters of Equipment	
Color/Logo	Customizable
Volume of Clean Water Tank	10,000 liters
Volume of Clean Waste Water Tank	
	High pressure water pump clean waster
Function	sluge and vacuum pump suction waste
	water waste garbage
Standard configuration	Clean water tank 10 cbm, Rust proof tank body, 6mm thick, with measuring pipes on the left and right sides for cleaning and preventing water ingress. Pinfu 330 flow high-pressure pump, sewage tank 10 cbm, 8mm thick, 4 partitions, partition sealing reinforcement, SK-12 water ring pump, pneumatic sewage discharge outlet at the tail 220, sewage discharge outlet at the tail 220, sewage pipe on the left and right sides of the tank, guardrail on the top of the tank, hydraulic suspension rod installation of 10 meter sewage suction pipe, with remote control, platform below the tank, and built-in top, The back cover can be opened, with 4 locks, and the tail coil is enlarged. Accessories: 200 meter high-pressure pipe, 10 combination nozzles.

ISUZU High Pressure Sewage Clean and Suction Truck Picture





Export



Hubei iTruck Import and Export Trading Co., Ltd







ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN