

Howo 8x4 50 Tons 25 Tons Integrated Wrecker Truck Underlift Tow Truck

Our Product Introduction

Basic Information

- Place of Origin: Hubei, China
- Brand Name: HOWO Sinotruck
- Minimum Order Quantity: 1
- Packaging Details: Nude, covered with film protection
- Delivery Time: 60 days
- Supply Ability: 5 sets per month



Product Specification

- Product Name: Integrated Wrecker Truck
- Transmission Type: Manual
- Dimensions (L X W X H) (mm): Customs Made
- Condition: New
- Subframe: Equipped
- Main Winch: 10 Tons, 2 Pcs
- Underlift: 3 Sections, Optional 4
- Underlift Tow Rating: 25 Ton/50 Tons
- Operation: Both Sides Manual
- Remote Control: Optional
- Warranty: 2 Year
- Highlight: 25 Tons Integrated Wrecker Truck, 8x4 Wrecker Truck, 25 Tons Underlift Tow Truck



for more products please visit us on hbitruck.com

Product Description

25 TONS HOWO 8X4 50 TONS TOW RATE 25 TONS RECOVERY BOOM INTEGRATED WRECKER TRUCK

Product Description

The heavy duty integrated series have different capacities from 20 tons to 50 tons.

BUILT FOR STRENGTH, RELIABILITY AND DURABILITY

The 25 tons integrated wrecker features a 44,500 lb. 2- or 3-stage wrecker boom, corrosion, resistant body and optional 3- or 4-stage underlifts – all designed with strength and performance in mind.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc.

With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

Main Features

1. 10 Tons / 22,200 lbs. Planetary Winch, 2 Pcs. Total 20 Tons / 44,500 lbs.
2. 25 Tons / 55,500 lbs. Underlift Capacity, Tow Rate At Least 50 Tons / 111,000 lbs.
3. Optional Remote Control
4. Sides Tool Boxes
5. Optional Front Legs and Side Pullers

Truck Specs

25 Tons HOWO Integrated Wrecker	
Overview	
Name	25 Tons HOWO Integrated Wrecker
Dimension(LxWxH)	11310x2500x3500(mm)
Total Mass	31000Kg
Kerb Weight	20770Kg
Passenger	3
Approach/Departure Angle	16/18
The Parameters of Chassis	
Manufacture/Model	HOWO
Driving Type	8*4 right hand drive
Wheel Base	1800+3000+1350 mm
Gearbox	HW19710,ten speed forward and two reverse, manual
Front/Rear Track	2022,2041,2022,2041/1830(mm)
Tyre	12.00R20
The Number of Tyre	12+1(spare tyre)
Front/Rear Suspension	1500/750(mm)
Leaf Spring Number	14,13/14,13/12
The Parameters of Engine	
Manufacturer/Model	HOWO/D10.38-30
Rated Power	380hp
Fuel Type	Diesel oil
Displacement/Capacity	9726ml
Emission Standard	Euro 3
Cylinder	In-line/6/watercooling/turbo charge/intercooling/common rail high pressure
Max. torque	1590N.m
Velocity	2000rpm

Body Specs

25 Tons Wrecker Body Specs				
No.	Item	Content	Details	Unit
1	Name	25 Tons Wrecker Body		
2	Winches	2×10 Tons Main Winches		Side puller/ extra winch is optional, extra USD2,500
3	Under lift	Under lift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 2 stage, hexagon	

5	Legs	Rear	Hydraulic rear supporting legs	Front supporting legs are extra USD3,500 or front outrigger extra USD5,000.
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control	Joystick type remote control, English Display, optional, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves		
		Cylinders		
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Primer and surface painting	All subframe with boom, under lift and tool box EP painting optional, extra USD2,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
		Packaging	Boxes and under lift protected for the painting	
Specifications				
1	Underlift	Retracted Lifting Capacity	25000	kg
		Retracted Length	1746	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3110	mm
		Undelift Tilt	-10	°
		Towing Capacity	50	ton
2	Boom	Retracted Lifting Capacity (45°)	20	ton
		Extended Lifting Capacity (45°)	12	ton
		Max. Lifting Tilt	33	°
		Max. Lifting Height	7022	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	10	ton
		Type	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	18	mm



ITRUCK
SPECIAL SERVICES

Hubei iTruck Import and Export Trading Co., Ltd

☎ 0086 19947597881

✉ alex@hbitruck.com

🌐 hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,
QINGSHAN DISTRICT, WUHAN