

6x6 30 Ton Rotator Wrecker Underlift Recovery Truck Safe Operation

Our Product Introduction

for more products please visit us on hbitruck.com

Basic Information

- Place of Origin: Hubei, China
- Brand Name: HOWO
- Minimum Order Quantity: 1
- Packaging Details: Nude, covered with protection film
- Delivery Time: 85 days
- Supply Ability: 5 unit/month



Product Specification

- Product Name: Rotator
- Condition: New
- Drive Type: 6x6 Driving
- Main Winch: 15 Tons, 2 Pcs
- Auxiliary Winch: Optional
- Underlift: G70, 3 Sections
- Boom: G70, 3 Sections
- Remote Control: Wireless
- Hydraulic: DOT Certified
- Warranty: 3 Year
- Highlight: 6x6 30 Ton Rotator Wrecker,
6x6 Underlift Recovery Truck,
safe operation 30 Ton Rotator Wrecker



More Images



Product Description

6X6 HOWO SINOTRUCK 30 TONS ROTATION TOW TRUCK ROTARY TOWING WRECKER TRUCK

Product Description

The rotator series has different capacities from 20 tons to 100 tons.

MAXIMUM STABILITY FOR MAXIMUM PERFORMANCE.

The strength and stability of the 30 tons rotator comes from the industry-leading scissor-style outriggers and unique frame design. The rotator also comes with standard joystick remote control, it supports stable and safe operation.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

Main Features

1. 15 Tons / 33,300 lbs. Planetary Winch, 2 Pcs, Total 30 Tons / 66,600 lbs. Optional Multi Drag and Turret Winches.
2. 20 Tons / 44,500 lbs. Underlift Capacity, Tow Rate At Least 40 Tons / 88,800 lbs. Underlift Boom 3 Stages.
3. Continuous Boom Rotation, Recovery Boom 3 Stage
4. Joystick Remote Control
5. Optional Aluminum Tool Boxes

Truck Specs

6x6 HOWO Rotator Truck	
Overview	
Name	6x6 HOWO Rotator Truck
Dimension(LxWxH)	10000x2500x3550 (mm)
Total Mass	31000Kg
Rated Payload	20000Kg
Kerb Weight	11000Kg
Passenger	3
Approach/Departure Angle	25/12
The Parameters of Chassis	
Manufacture/Model	HOWO
Driving Type	6*6 RHD/LHD
Wheel Base	4600+1350 mm
Gearbox	HW19710, ten speed forward and two reverse, manual
Front/Rear Track	2022,2041/1830,1830(mm)
Tyre	13R22.5 triangle
The Number of Tyre	10+1(spare tyre)
Front/Rear Suspension	1500/850(mm)
The Parameters of Engine	
Manufacturer/Model	Weichai/WD615.47
Rated Power	371hp
Fuel Type	Diesel oil
Displacement/Capacity	9726ml
Emission Standard	Euro 2
Cylinder	Straight/6/intercooling
Max. torque	1500N.m
Velocity	2200rpm

Body Specs

30 Tons Rotator Wrecker Specs				
No.	Item	Content	Details	Unit
1	Name	30 Tons Rotator Wrecker		
2	Winches	2×15 Tons Main Winches		Additional winches are optional
3	Under lift	Under lift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 3 stage	
5	Legs	Hydraulic	Hydraulic rear and front supporting legs	
6	Frame	LED Lights Frame, full size		

7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control	Joystick type chest mount, English Display, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump	Double pump	
		Hydraulic Hose		
		Hose Connector		
		Valves	Italy	
		Cylinders		
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting, other normal painting	All subframe with boom and under lift EP painting optional, extra USD1,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Specifications				
1	Underlift	Retracted Lifting Capacity	20000	kg
		Retracted Length	1746	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3492	mm
		Undelift Tilt	-10	°
		Towing Capacity	40	ton
2	Boom	Retracted Lifting Capacity (45°)	30	ton
		Extended Lifting Capacity (45°)	9	ton
		Max. Lifting Tilt	65	°
		Max. Lifting Height	11529	mm
		Boom Hook(Max. Lifting Height)Away from Underlift(Folding)	5219	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	15	ton
		Type	Planetary	
		Steel Wire Length	60	m
		Steel Wire Diameter	18	mm





0086 19947597881



alex@hbitruck.com



hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,
QINGSHAN DISTRICT, WUHAN