4x4 Dongfeng RHD LHD Underlift Recovery Truck 16 Tons 18 Tons

Basic Information

Place of Origin: Hubei, ChinaBrand Name: Dongfeng

Minimum Order Quantity:

• Packaging Details: Nude, covered with protection film

Delivery Time: 85 daysSupply Ability: 5 unit/month



Product Specification

Product Name: Integrated Wrecker Truck

• Condition: New

• Drive Type: 4x4 Driving

• Main Winch: 8 Tons/10 Tons, 2 Pcs

Auxiliary Winch: Optional

Underlift: G70, 3 SectionsBoom: G70, 2 Sections

Remote Control: WirelessHydraulic: DOT CertifiedWarranty: 3 Year

• Highlight: Underlift Recovery Truck 16 Tons,

Underlift Recovery Truck 18 Tons, 18 Tons underlift tow truck



More Images







Product Description

4X4 DONGFENG RHD LHD 16 TONS 18 TONS UNDERLIFT RECOVERY TRUCK

Product Description

The medium duty integrated series have different capacities from 8 tons to 18 tons.

ENGINEERED FOR STRENGTH AND DURABILITY

The 16 ton Integrated Medium Duty wrecker with a 35,600 lb. rated underlift and a modern, steel body that is maximized for available storage and deck space.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

Main Features

- 1. 10 Tons / 22,200 lbs. Planetary Winch, 2 Pcs. Total 20 Tons / 44,500 lbs.
- 2. 12 Tons / 26,700 lbs. Underlift Capacity, Tow Rate At Least 24 Tons / 53,300 lbs.
- 3. Spacious Tool Compartments
- 4. Multi-Positional Rear Jacks
- 5. Optional Remote Control
- 6. Available Low Profile Tow Bar

Body Specs

16 T	ons Wrecker	Body Specs		
No.	Item	Content	Details	Unit
1	Name	16 Tons Wrecker Body		
2	Winches	2×10 Tons Main Winches		Side puller (10 tons) is optional, extra USD2,500
3	Underlift	Underlift	G70 material, 3 stage	
4	Boom	Boom	G70 material, 2 stage, hexagon	
5	Legs	Rear	Hydraulic rear supporting legs	Front support legs are optional. Extra USD3,000
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD4,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Standard button remote control.	Optional Joystick type remote control, English Display Extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves	Italy Hydrocontrol	
		Cylinders		
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting	Subframe with boom and underlift EP painting extra USD1,500
	<u> </u>	Surface Painting	Epoxy Resin	1
		Indication	English Indication and Marks	
Spe	cifications			•
1	Underlift	Retracted Lifting Capacity	12000	kg
		Retracted Length	1505	mm

		Extended Lifting Capacity	4200	kg
		Extended Length	2760	mm
		Undelift Tilt	-10	٥
		Towing Capacity	24-36	ton
2	Boom	Retracted Lifting Capacity (45°)	18	ton
		Extended Lifting Capacity (45°)	6.3	ton
3	Main Winches	Quantity	2	pcs
		Pulling Power	10	ton
		Туре	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	18	mm



Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881





ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN