4x2 Foton 220hp Cummins Engine 12 Ton Tow Truck Towing Vehicle

Basic Information

Place of Origin: Hubei, China
Brand Name: Foton
Minimum Order Quantity: 1

Packaging Details: Nude, covered with protection film

Delivery Time: 85 daysSupply Ability: 5 unit/month



Product Specification

Product Name: Integrated Wrecker Truck

• Condition: New

• Drive Type: 4x2 Driving

• Main Winch: 8 Tons/10 Tons, 2 Pcs

Auxiliary Winch: Optional

Underlift: G70, 3 SectionsBoom: G70, 2 Sections

Remote Control: WirelessHydraulic: DOT CertifiedWarranty: 3 Year

• Highlight: Cummins Engine 12 Ton Tow Truck,

220hp 12 Ton Tow Truck, Cummins Engine Towing Vehicle



Product Description

4X2 FOTON 220HP CUMMINS ENGINE 12 TONS INTEGRATED TOW TRUCK

Product Description

The medium duty integrated series have different capacities from 8 tons to 18 tons.

ENGINEERED FOR STRENGTH AND DURABILITY

The 12 ton Integrated Medium Duty wrecker with a 17,800 lb. rated underlift and a modern, steel body that is maximized for available storage and deck space.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

Main Features

- 1. 8 Tons / 17,800 lbs. Planetary Winch, 2 Pcs. Total 16 Tons / 35,600 lbs.
- 2. 8 Tons / 17,800 lbs. Underlift Capacity, Tow Rate At Least 16 Tons / 35,600 lbs.
- 3. Spacious Tool Compartments
- 4. Multi-Positional Rear Jacks
- 5. Optional Remote Control
- 6. Available Low Profile Tow Bar

Truck Specs

12 Tons Foton Wrecker Truck						
Overview						
Name	12 Tons Foton Wrecker Truck					
Dimension(LxWxH)	8250x2250x2655(mm)					
Total Mass	16510Kg					
Rated Payload	12000Kg					
Kerb Weight	4510Kg					
Passenger	3					
Approach/Departure Angle	30/23					
The Parameters of Chassis						
Manufacture/Model	Foton					
Driving Type	4*2 LHD/RHD					
Wheel Base	5150 mm					
Gearbox	FAST 8JS85T, eight speed forward and two					
	reverse, manual					
Front/Rear Track	1914/1800(mm)					
Tyre	10.00R20					
The Number of Tyre	6+1(spare tyre)					
Front/Rear Suspension	1250/2320(mm)					
Leaf Spring Number	4+3					
Fuel Tank	260L Aliminum					
Power Steer, AC, Air Brake, MP3, ABS, etc	Equipped					
The Paremeters of Engine						
Manufacturer/Model	Cummins/ISF4.5 210					
Rated Power	210hp					
Fuel Type	Diesel oil					
Displacement/Capacity	4460ml					
Emission Standard	Euro 5					
Cylinder	In-line/4/intercooling/turbo charge/Bosch common rail/pressure direct injection					
Max. torque	760N.m					
Velocity	2300rpm					

Body Specs

12 Tons Wrecker Body Specs						
No.	Item	Content	Details	Unit		
1	Name	12 Tons Wrecker Body				
2	Winches	2×8 Tons Main Winches		Side puller (8 tons) is optional, extra USD2,000		
3	Underlift	Underlift	G70 material, 3 stage			
	•	•	•	*		

4	Boom	Boom	G70 material, 2 stage, hexagon	
5	Legs	Rear	Hydraulic rear supporting legs	Front support legs are optional. Extra USD1,500
6	Frame	LED Lights Frame, full size		
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD3,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Optional button remote control. Extra USD1,000	Optional Joystick type remote control, English Display Extra USD3,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves	Italy Hydrocontrol	
		Cylinders		
11	Attachments	s5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Toolbox EP painting	Subframe with boom and underlift EP painting extra USD1,200
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
Spe	cifications			
1	Underlift	Retracted Lifting Capacity	8000	kg
		Retracted Length	1505	mm
		Extended Lifting Capacity	3500	kg
		Extended Length	2760	mm
		Undelift Tilt	-10	0
		Towing Capacity	16-24	ton
2	Boom	Retracted Lifting Capacity (45°)	12	ton
		Extended Lifting Capacity (45°)	5.5	ton
3	Main Winches	Quantity	2	pcs
		Pulling Power	8	ton
		Туре	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	16	mm





alex@hbitruck.com

hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN