Howo Sinotruck 310hp 16 Tons Medium Duty Tow Truck 4x2 Euro 6 LHD

Basic Information

- Place of Origin:
- Hubei, China
- Brand Name:
- HOWO Sinotruck
- Minimum Order Quantity:
- Packaging Details:Delivery Time:
- Supply Ability:
- 1 Nude, covered with protection film
- 85 days
- 5 unit/month



Our Product Introduction

Product Specification

- Product Name:
- Condition:
- Drive Type:
- Main Winch:
- Auxiliary Winch:
- Underlift:
- Boom:
- Remote Control:
- Hydraulic:
- Warranty:
- Highlight:

- Integrated Wrecker Truck
- New 4x2 Driving
- 8 Tons/10 Tons, 2 Pcs
- Optional
- G70, 3 Sections
- G70, 2 Sections
- Wireless
- DOT Certified
- 3 Year
 - 310hp Medium Duty Tow Truck, Medium Duty Tow Truck Euro 6, 16 ton tow truck Euro 6



More Images









Product Description

4X2 HOWO SINOTRUCK EURO 6 LHD 310HP 16 TONS MEDIUM DUTY TOW TRUCK

Product Description

The medium duty integrated series have different capacities from 8 tons to 18 tons.

ENGINEERED FOR STRENGTH AND DURABILITY

The 16 ton Integrated Medium Duty wrecker with a 35,600 lb. rated underlift and a modern, steel body that is maximized for available storage and deck space.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8. Other special requirements you want.

Main Features

- 1. 10 Tons / 22,200 lbs. Planetary Winch, 2 Pcs. Total 20 Tons / 44,500 lbs.
- 2. 16 Tons / 35,600 lbs. Underlift Capacity, Tow Rate At Least 32 Tons / 71,000 lbs.
- 3. Spacious Tool Compartments
- 4. Multi-Positional Rear Jacks
- 5. Optional Remote Control
- 6. Available Low Profile Tow Bar

Truck Specs

16 Tons HOWO Integrated Wrecker Truck			
Overview			
Name	16 Tons HOWO Integrated Wrecker Truck		
Dimension (LxWxH)	8950,9350,9100,9500×2550×3030(mm)		
Total Mass	18000 Kg		
Rated Payload	7170 Kg		
Kerb Weight	15930 Kg		
Passenger	3		
Approach/Departure Angle	17/13		
The Parameters of Chassis			
Manufacture/Model	HOWO		
Driving Type	4*2 left hand drive		
Wheel Base	5600 mm		
Gearbox	Ten speed forward and two reverse, manual		
Tyre	10.00R20		
The Number of Tyre	6+1(spare tyre)		
Axles	Front 6.5 tons and rear double 11.5 tons		
Electric chair, ABS, power window, AC, power steer, clutch booster, air brake, etc.	Equipped		
The Parameters of Engine			
Manufacturer/Model	MAN/MC07.31-60		
Rated Power	310hp		
Fuel Type	Diesel oil		
Displacement/Capacity	6870 ml		
Emission Standard	Euro 6		
Cylinder	In-line/6/turbo/inter- cooling/EGR+DOC+DPF+SCR/high pressure common rail		
Max. Torque	1230 N.m		
Rated Velocity	2200rpm		

Body Specs

No.	ons Wrecker	Content	Details	Unit
1	Name	16 Tons Wrecker Body		
				Side puller (10 tons)
2	Winches	2×10 Tons Main Winches		is optional,
	VVIII CIICS			extra USD2,500
3	Underlift	Underlift	G70 material, 3 stage	
	Ondernit	Ondernit	G70 material, 2 stage,	
4	Boom	Boom	hexagon	
				Front support legs
5	Legs	Rear	Hydraulic rear supporting	are optional.
	Legs		legs	Extra USD3,000
6	Frame	LED Lights Frame, full size		
0	i iame			Aluminum tool box
7	Laghay	On Both Sides	Carbon steel Q345R, with	
	Toolbox	On Both Sides	stainless steel handles	optional, extra USD4,000
0		Air and Electrical Llock Lloc	12V or 24V	
8	Hook-Ups	Air and Electrical Hook-Ups	12 V OF 24 V	Outienel levetiel
				Optional Joystick
9	Control	Remote Wireless Control	Standard button remote	type remote control,
			control.	English Display Extr
				USD2,000
			On Lift and Right Sides,	
		Hand Manual Control	English	
	Uburlas P		Indication	
10	Hydraulic	Hydraulic Pump		
	Parts			
		Hydraulic Hose		
		Hydraulic Connector		
		Valves	Italy Hydrocontrol	
		Cylinders		
11	Attachmonto	5 Sets of Forks	4 sets for axle, 1 set for	
	Allachinenis		suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
	D · ··		· · · · · · · · · · · · · · · · · · ·	Subframe with boon
	Painting			and underlift
12	and	Electrophoresis Painting	Toolbox EP painting	EP painting extra
	Indication			USD1,500
		Surface Painting	Epoxy Resin	
			English Indication and	
		Indication	Marks	
Sno	cifications		Marto	
		Retracted Lifting Capacity	12000	ka
1	Undernit	Retracted Length		kg
			1505	mm
	-	Extended Lifting Capacity	4200	kg
		Extended Length	2760	mm
		Undelift Tilt	-10	0
		Towing Capacity	24-36	ton
~	Desau	Retracted Lifting Capacity	10	
2	Boom	(45°)	18	ton
		Extended Lifting Capacity	1	
		(45°)	6.3	ton
	Main			
3	Winches	Quantity	2	pcs
	winches	Pulling Power	10	ton
		Pulling Power	10 Dispeters	ton
		Type	Planetary	
		Steel Wire Length	45	m
	1	Steel Wire Diameter	18	mm



Image: Second state of the second s