# Iveco Heavy Duty 25 Ton Wrecker 50 Ton Tow Truck 6x4 Driving New **Condition**

### **Basic Information**

. Place of Origin: Hubei, China • Brand Name: Iveco • Minimum Order Quantity:

Nude, covered with protection film Packaging Details:

• Delivery Time: 85 days • Supply Ability: 5 unit/month



# **Product Specification**

• Product Name: Integrated Wrecker Truck

6x4 Driving

Condition:

• Drive Type: • Main Winch: 10 Tons, 2 Pcs Auxiliary Winch: Optional • Underlift: G70, 3 Sections • Boom: G70, 2 Sections

• Remote Control: Wireless **DOT** Certified Hydraulic:

3 Year • Warranty:

Highlight: Iveco 25 Ton Wrecker, 25 Ton Wrecker 6x4 Driving,

Iveco 50 Ton Tow Truck



### **Product Description**

# 6X4 IVECO 25 TONS WRECKER TOWING TRUCK 50 TON TOW RATE HEAVY DUTY WRECKER TOW TRUCK Product Description

The heavy duty integrated series have different capacities from 20 tons to 50 tons.

### BUILT FOR STRENGTH, RELIABILITY AND DURABILITY

The 25 tons integrated wrecker features a 44,500 lb. 2- or 3-stage wrecker boom, corrosion, resistant body and optional 3- or 4-stage underlifts – all designed with strength and performance in mind.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD. With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

#### **Main Features**

- 1. 10 Tons / 22,200 lbs. Planetary Winch, 2 Pcs. Total 20 Tons / 44,500 lbs.
- 2. 25 Tons / 55,600 lbs. Underlift Capacity, Tow Rate At Least 50 Tons / 111,100 lbs.
- 3. Optional Remote Control
- 4. Sides Tool Boxes
- 5. Optional Front Legs and Side Pullers

### **Truck Specs**

6x4 IVECO Wrecker Truck						
Overview						
Name	6x4 IVECO Wrecker Truck					
Dimension (LxWxH)	10730×2550×3120 (mm)					
Total Mass	25000Kg					
Kerb Weight	21000Kg					
Passenger	3					
The Parameters of Chassis						
Manufacture/Model	IVECO					
Driving Type	6*4 left hand drive					
Wheel Base	4400+1350 mm					
Gearbox	FAST RT-11509C, nine speed forward and one					
Gearbox	reverse, manual					
Tyre	12.00R20					
The Number of Tyre	10+1(spare tyre)					
Frame	940-865/317/8+8					
Alexs	Rear 16 tons double					
Oil Tank	200L tank					
The Parameters of Engine	•					
Manufacturer/Model	/Model Cursor/C9 290					
Rated Power	290hp					
Fuel Type	Diesel oil					
Displacement/Capacity	8709ml					
Emission Standard	Euro 3					
Cylinder	Straight/6/turbo charge					
Max. torque	1250N.m					
Velocity	2100rpm					

## **Body Specs**

25 Tons Wrecker Body Specs						
No.	Item	Content	Details	Unit		
1	Name	25 Tons Wrecker Body				
2	Winches	2×10 Tons Main Winches		Side puller/ extra winch is optional, extra USD2,500		
3	Under lift	Under lift	G70 material, 3 stage			
4	Boom	Boom	G70 material, 2 stage, hexagon			
5	Legs	iBear	Hydraulic rear supporting legs	Front supporting legs are extra USD3,500 or front outrigger extra USD5,000.		
6	Frame	LED Lights Frame, full size				

7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles	Aluminum tool box optional, extra USD5,000
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V	
9	Control	Remote Wireless Control	Button remote control	Joystick type remote control, English Display, optional, extra USD2,000
		Hand Manual Control	On Lift and Right Sides, English Indication	
10	Hydraulic Parts	Hydraulic Pump		
		Hydraulic Hose		
		Hydraulic Connector		
		Valves		
		Cylinders		
11	Attachment s	5 Sets of Forks	4 sets for axle, 1 set for suspension	
		U shape tyres holder	1 set	
		Safety Chains	2 pcs	
12	Painting and Indication	Electrophoresis Painting	Primer and surface painting	All subframe with boom, under lift and tool box EP painting optional, extra USD2,500
		Surface Painting	Epoxy Resin	
		Indication	English Indication and Marks	
		Packaging	Boxes and under lift protected for the painting	
Spe	cifications			
1	Underlift	Retracted Lifting Capacity	25000	kg
		Retracted Length	1746	mm
		Extended Lifting Capacity	7310	kg
		Extended Length	3110	mm
		Undelift Tilt	-10	0
		Towing Capacity	50	ton
2	Boom	Retracted Lifting Capacity (45°)	20	ton
		Extended Lifting Capacity (45°)	12	ton
		Max. Lifting Tilt	33	0
		Max. Lifting Height	7022	mm
3	Main Winches	Quantity	2	pcs
		Pulling Power	10	ton
		Туре	Planetary	
		Steel Wire Length	45	m
		Steel Wire Diameter	18	mm



ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN