# 10x6 Shacman Heavy Duty Wrecker Tow Truck 40 Tons 50 Tons Subframe Equipped

## **Basic Information**

Place of Origin: Hubei, ChinaBrand Name: Shacman

Minimum Order Quantity:

• Packaging Details: Nude, covered with film protection

• Delivery Time: 60 days

• Supply Ability: 5 sets per month



# **Product Specification**

Product Name: Integrated Wrecker Truck

• Transmission Type: Manual

• Dimensions (L X W X H) Customs Made

(mm):

• Operation:

• Condition: New

• Subframe: Equipped

Main Winch: 20/25 Tons, 2 Pcs
Underlift: 3 Sections, Optional 4
Underlift Tow Rating: 25 Ton/50 Tons

Remote Control: OptionalWarranty: 2 Year

• Highlight: Shacman Heavy Duty Wrecker Tow Truck,

Both Sides Manual

10x6 Heavy Duty Wrecker Tow Truck, Heavy Duty Wrecker Subframe Equipped



## More Images









## **Product Description**

## 10X6 SHACMAN 40 TONS 50 TONS HEAVY WRECKER HEAVY DUTY INTEGRATED TOWING

#### **Product Description**

The heavy duty integrated series have different capacities from 30 tons to 50 tons.

The heavy duty integrated wrecker features a 66,000 lb. - 111,000 lb. 2- or 3-stage wrecker boom, corrosion, resistant body and optional 3- or 4-stage underlifts – all designed with strength and performance in mind.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

#### **Main Features**

- 1. 15 Tons / 33,200 lbs. 25 Tons / 55,000 lbs. Planetary Winch, 2 Pcs. Total 30 Tons / 66,600 lbs 50 Tons / 111,000 lbs.
- 2. 28 Tons / 62,200 lbs. Underlift Capacity, Tow Rate At Least 56 Tons / 124,000 lbs.
- 3. Optional Remote Control
- 4. Sides Tool Boxes
- 5. Optional Front Legs and Side Pullers

#### **Truck Specs**

10x6 Shacman Wrecker Truck			
Overview			
Name	10x6 Shacman Wrecker Truck		
Dimension (LxWxH)	11950x2550x3950 (mm)		
Total Mass	42800Kg		
Rated Payload	25000Kg		
Kerb Weight	17800Kg		
Passenger	3		
The Parameters of Chassis			
Manufacture/Model	Shacman		
Driving Type	10*6 RHD/LHD		
Wheel Base	2100+3175+1400+1400 mm		
Gearbox	10JSD180+QH50, ten speed forward and two		
Gearbox	reverse, manual		
Tyre	12.00R20		
The Number of Tyre	14+1(spare tyre)		
Frame	850x300(8+5+8)		
Alexs	Front 9.5 tons and rear 16 tons, MAN		
Oil Tank	300L aluminum tank		
The Parameters of Engine	·		
Manufacturer/Model	WeiChai/WP10.380E22		
Rated Power	380hp		
Fuel Type	Diesel oil		
Displacement/Capacity	9726ml		
Emission Standard	Euro 2		
Cylinder	Straight/6/turbo		
	charge/intercooling/watercooling/direct injection		
Max. torque	1600N.m		
Velocity	2200rpm		

### **Body Specs**

Vo.	Item	Content	Details	Details	Details		
	Name		30 Tons Wrecker Body	40 Tons Wrecker Body	50 Tons Wrecker Body		
2	Winches		2×15 Tons Main Winches	2×20 Tons Main Winches	2×25 Tons Main Winches		
3	Under lift	Under lift	G70 material, 3-4 stage		1		
1	Boom	Boom	G70 material, 2-3 stage, hexagon				
5	Legs	Rear	Hydraulic rear supporting legs				
6	Frame	LED Lights Frame, full size					
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles				
3	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V				
9	Control	Remote Wireless Control	Button remote control				
		Hand Manual Control	On Lift and Right Sides, English Indication				
10	Hydraulic Parts	Hydraulic Pump	Double Pump				
		Hydraulic Hose					
		Hydraulic					
		Connector	lu-L.				
		Valves	Italy				
	Attachment	Cylinders					
11	s		4 sets for axle, 1 set for suspension				
		U shape tyres holder	1 set				
	Deinting	Safety Chains	2 pcs				
12	Painting and Indication	Electrophoresis Painting	Tool Box EP painting, other normal painting				
	i i	Surface Painting					
		Indication	English Indication and Marks				
		Packaging	Boxes and under lift pro	tected for the painting			
Spe	cifications						
1	Underlift	Сараспу	25000	28000	28000		
		Retracted Length		1746	1746		
		Capacity	7310	7310	7310		
		Extended Length		3410	3410		
		Undelift Tilt	-10	-10	-10		
		D : 11''''	50	56	56		
	Doom	Retracted Lifting	30	40	50		
2	Boom	Capacity (45°)		1.0			
2		Capacity (45°) Extended Lifting Capacity (45°)	8	10	11.5		
2		Capacity (45°) Extended Lifting Capacity (45°) Max. Lifting Tilt			11.5 33		
2		Capacity (45°) Extended Lifting Capacity (45°)	8	10			
	Main Winches	Capacity (45°) Extended Lifting Capacity (45°) Max. Lifting Tilt Max. Lifting Height Quantity	8 33 7022 2	10 33 7022 2	33 7022 2		
	Main Winches	Capacity (45°) Extended Lifting Capacity (45°) Max. Lifting Tilt Max. Lifting Height Quantity Pulling Power	8 33 7022 2 15	10 33 7022 2 20	33 7022 2 25		
2 33	Main Winches	Capacity (45°) Extended Lifting Capacity (45°) Max. Lifting Tilt Max. Lifting Height Quantity Pulling Power Type	8 33 7022 2	10 33 7022 2	33 7022 2		
	Main Winches	Capacity (45°) Extended Lifting Capacity (45°) Max. Lifting Tilt Max. Lifting Height Quantity Pulling Power	8 33 7022 2 15	10 33 7022 2 20	33 7022 2 25		





## Hubei iTruck Import and Export Trading Co., Ltd







ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN