

## Customs Made Sinotruck 40 Ton Tow Truck Wheel Lift 10x6 Driving

Our Product Introduction

### Basic Information

- Place of Origin: Hubei, China
- Brand Name: HOWO
- Minimum Order Quantity: 1
- Packaging Details: Nude, covered with film protection
- Delivery Time: 60 days
- Supply Ability: 5 sets per month



### Product Specification

- Product Name: Integrated Wrecker Truck
- Transmission Type: Manual
- Dimensions (L X W X H) (mm): Customs Made
- Condition: New
- Subframe: Equipped
- Main Winch: 20/25 Tons, 2 Pcs
- Underlift: 3 Sections, Optional 4
- Underlift Tow Rating: 25 Ton/50 Tons
- Operation: Both Sides Manual
- Remote Control: Optional
- Warranty: 2 Year
- Highlight: Customs Made 40 Ton Tow Truck, 40 Ton Tow Truck 10x6 Driving, 10x6 Driving recovery tow trucks



for more products please visit us on [hbitruck.com](http://hbitruck.com)

## Product Description

### 10X6 SINOTRUCK 40 TONS TOW TRUCK WHEEL LIFT 50 TON TOW TRUCKS & WRECKERS

#### Product Description

The heavy duty integrated series have different capacities from 30 tons to 50 tons.

The heavy duty integrated wrecker features a 66,000 lb. - 111,000 lb. 2- or 3-stage wrecker boom, corrosion, resistant body and optional 3- or 4-stage underlifts – all designed with strength and performance in mind.

The truck brand options also available with ISUZU, Dongfeng, HOWO, JAC, FOTON, JMC, FAW, SHACMAN, IVECO, etc. With Euro 2, Euro 3, Euro 5, Euro 6 emission.

With RHD, LHD.

With 4x2, 4x4, 6x4, 6x6, 8x4, 8x8.

Other special requirements you want.

#### Main Features

1. 15 Tons / 33,200 lbs. - 25 Tons / 55,000 lbs. Planetary Winch, 2 Pcs. Total 30 Tons / 66,600 lbs - 50 Tons / 111,000 lbs.
2. 28 Tons / 62,200 lbs. Underlift Capacity, Tow Rate At Least 56 Tons / 124,000 lbs.
3. Optional Remote Control
4. Sides Tool Boxes
5. Optional Front Legs and Side Pullers

#### Truck Specs

50 Tons HOWO Integrated Wrecker Truck	
Overview	
Name	50 Tons HOWO Integrated Wrecker Truck
Dimension(LxWxH)	11310x2500x3500(mm)
Total Mass	31000Kg
Kerb Weight	20770Kg
Passenger	3
Approach/Departure Angle	16/18
The Parameters of Chassis	
Manufacture/Model	HOWO
Driving Type	10*6 RHD/LHD
Wheel Base	1800+3000+1350+1350 mm
Gearbox	HW19710,ten speed forward and two reverse, manual
Front/Rear Track	2022,2041,2022,2041/1830(mm)
Tyre	12.00R20
The Number of Tyre	14+1(spare tyre)
Front/Rear Suspension	1500/750(mm)
Leaf Spring Number	14,13/14,13/12
The Parameters of Engine	
Manufacturer/Model	HOWO/D10.38-30
Rated Power	380hp
Fuel Type	Diesel oil
Displacement/Capacity	9726ml
Emission Standard	Euro 3
Cylinder	In-line/6/watercooling/turbo charge/intercooling/common rail high pressure
Max. torque	1590N.m
Velocity	2000rpm

#### Body Specs

Heavy Duty Integrated Wrecker Body					
No.	Item	Content	Details	Details	Details
1	Name		30 Tons Wrecker Body	40 Tons Wrecker Body	50 Tons Wrecker Body
2	Winches		2×15 Tons Main Winches	2×20 Tons Main Winches	2×25 Tons Main Winches
3	Under lift	Under lift	G70 material, 3-4 stage		
4	Boom	Boom	G70 material, 2-3 stage, hexagon		
5	Legs	Rear	Hydraulic rear supporting legs		
6	Frame	LED Lights Frame, full size			
7	Toolbox	On Both Sides	Carbon steel Q345R, with stainless steel handles		
8	Hook-Ups	Air and Electrical Hook-Ups	12V or 24V		
9	Control	Remote Wireless Control	Button remote control		
		Hand Manual Control	On Lift and Right Sides, English Indication		
10	Hydraulic Parts	Hydraulic Pump	Double Pump		
		Hydraulic Hose			
		Hydraulic Connector			
		Valves	Italy		
		Cylinders			
11	Attachments	5 Sets of Forks	4 sets for axle, 1 set for suspension		
		U shape tyres holder	1 set		
		Safety Chains	2 pcs		
12	Painting and Indication	Electrophoresis Painting	Tool Box EP painting, other normal painting		
		Surface Painting	Epoxy Resin		
		Indication	English Indication and Marks		
		Packaging	Boxes and under lift protected for the painting		
Specifications					
1	Underlift	Retracted Lifting Capacity	25000	28000	28000
		Retracted Length	1746	1746	1746
		Extended Lifting Capacity	7310	7310	7310
		Extended Length	3110	3410	3410
		Undelift Tilt	-10	-10	-10
		Towing Capacity	50	56	56
2	Boom	Retracted Lifting Capacity (45°)	30	40	50
		Extended Lifting Capacity (45°)	8	10	11.5
		Max. Lifting Tilt	33	33	33
		Max. Lifting Height	7022	7022	7022
3	Main Winches	Quantity	2	2	2
		Pulling Power	15	20	25
		Type	Planetary	Planetary	Planetary
		Steel Wire Length	45	45	45
		Steel Wire Diameter	18	26	28



**ITRUCK**  
SPECIAL SERVICES

**Hubei iTruck Import and Export Trading Co., Ltd**



0086 19947597881



alex@hbitruck.com



hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,  
QINGSHAN DISTRICT, WUHAN