# 4x2 Japanese ISUZU NPR KV600 Garbage Compacted Truck With 6 Cbm To 8 Cbm Volume

### **Basic Information**

Place of Origin: HubeiBrand Name: ISUZUCertification: ccc

Model Number: QL1072A5KAY

Minimum Order Quantity:

• Price: 32500\$

Packaging Details: nude with waxing
Delivery Time: 30-35 working days
Payment Terms: Western Union, T/T, L/C
Supply Ability: 50 units per month



# **Product Specification**

Brand Name: ISUZU Garbage TruckVolume: 6000 To 8000 Liters

Chassis Model: ISUZU

Engine: 4KH1CN5HSWheelbase: 3360 Mm

Contorl: Electric And Hydraulic

Drive Model: 4x2
Tire: 7.00R15
Transmission: MSB5
Emission Standard: Eu 5 To Eu 6

Highlight: 6 cbm garbage compacted truck,

4x2 garbage compacted truck, 8 cbm garbage compacted truck



# More Images









#### **Product Description**

#### 4x2 Japanese ISUZU KV600 NPR garbage compacted truck with 6 cbm volume

Garbage trucks are mainly used for collecting, loading, and transporting household waste, and can compress and crush the loaded garbage to increase its density and reduce its volume, greatly improving the efficiency of garbage collection and transportation. The new garbage truck has the characteristics of reliable quality, low failure rate, easy maintenance, and low operating costs.

Garbage trucks can be further classified into various types based on their collection methods, including but not limited to:

Compressed garbage truck: using a mechanical, electrical, hydraulic linkage control system, computer control, and manual operation system, garbage is poured, crushed, or flattened through devices such as fillers and shovels, and garbage is squeezed into the compartment, compacted, and pushed out.

Self dumping garbage truck: equipped with a hydraulic system that can tilt the carriage to a certain angle and dump the garbage on its own.

Swing arm garbage truck: composed of chassis, garbage bin (hopper), swing arm deceleration buffer oil cylinder, etc. Its characteristic is that the garbage bin can be separated from the vehicle body, realizing the joint use of one vehicle and multiple garbage bins.

Sealed garbage truck: widely used for urban street garbage treatment, with sealed self dumping function, hydraulic operation, and convenient dumping of garbage.

Hanging bucket self loading and unloading garbage truck: using a chain and hydraulic cylinder linkage device to achieve semi lifting and flipping of garbage, automatically collecting garbage from multiple garbage bins into the carriage, and self dumping.

These different types of garbage trucks each have their own unique advantages and application scenarios, which can meet the garbage treatment needs in different environments and are important tools for maintaining urban hygiene and appearance

#### Main Technical specification

| Overview                          |                                 |
|-----------------------------------|---------------------------------|
| Name                              | 6 cbm ISUZU Garbage Compactor   |
|                                   | Truck                           |
| Dimension(LxWxH)                  | 7000x2250x2750 mm               |
| Total Mass                        | 8800 kg                         |
| Rated Payload                     | 4500 kg                         |
| Kerb Weight                       | 4200 kg                         |
| Passenger                         | 3                               |
| Approach/Departure Angle          | 15°/12 °                        |
| The Parameters of Chassis         |                                 |
| Manufacture/Model                 | ISUZU /4KH1CN5HS                |
| Driving Type                      | 4x2                             |
| Wheel Base                        | 3815 mm                         |
| Gearbox                           | MSB5                            |
| Front/Rear Track                  | 1676/1620 mm                    |
| Tyre model                        | 7.50R15                         |
| The Number of Tyre                | 6+1 (spare tyre)                |
| Front/Rear Suspension             | 1430/2280 mm                    |
| The Parameters of Engine          | •                               |
| Manufacturer/Model                | 4KH1CN5HS                       |
| Rated Power                       | 96kw/130hp                      |
| Fuel Type                         | Diesel oil                      |
| Displacement/Capacity             | 2982 ml                         |
| Emission Standard                 | Eu 5                            |
| Cylinder                          | 4                               |
| Max. Torque/ speed                | 290 N.m/ 1500rpm                |
| Velocity                          | 3400 rpm                        |
| The Parameters of Equipment       |                                 |
| Color/Logo                        | Customized                      |
| Volume of Tank                    | 6,000 liters                    |
| Function                          | Delivery life use waste garbage |
| Compressor and filling cycle time | 25-30 s                         |
| Loading cycle time                | 17-25 s                         |
| Discharge cycle time              | 30-45 s                         |
|                                   |                                 |

| Compressor density  | 0.6-0.8 kg/m <sup>3</sup>   |
|---------------------|---|
| Rear loading device | Flip board/triangulation/swinging arm   |
| Others              | High strength Q345 manganese steel ,steel plate thickness bottom 5mm, side 4mm, tail bilateral sewage tank, manual control. Electric operation and cab control. Rear loading plastic, hopper and swing arm bucket |

ISUZU Garbage Compacotr Truck Picture













Garbage Compactor Truck Working Stock







Export













Hubei iTruck Import and Export Trading Co., Ltd



0086 19947597881



alex@hbitruck.com



hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN