

5 TONS DONGFENG RHD LHD REFRIGERATED TRUCK FOR TRANSPORTATION

Our Product Introduction

Basic Information

- Place of Origin: Hubei
- Brand Name: Dongfeng
- Certification: ccc
- Minimum Order Quantity: 1
- Packaging Details: nude with waxing
- Delivery Time: 15 working days
- Payment Terms: L/C, T/T, D/P, Western Union
- Supply Ability: 50 units per month



Product Specification

- Name: Refrigerator Van Truck
- Drive Model: 4x2
- Box Dimension: 4100x2000x2000 Mm
- Wheelbase: 3360 Mm
- Loading Capacity: 3-5 Tons
- Lowest Temperature: -15 Cent Degree
- Tire: 7.00R16
- Transmission: 5/1
- Power Steer: Yes
- Air Condition: Yes
- Highlight: **LHD REFRIGERATED TRUCK,
5 TONS REFRIGERATED TRUCK,
DONGFENG REFRIGERATED TRUCK**



for more products please visit us on hbitruck.com

Product Description

4 TONS DONGFENG RHD LHD REFRIGERATED TRUCK FOR TRANSPORTATION

Refrigerated truck

A refrigerated truck is a closed box type transport vehicle used to transport frozen or fresh goods. It is a specialized refrigerated transport vehicle equipped with a refrigeration unit and a polyurethane insulated compartment. It is commonly used to transport frozen food (refrigerated truck), dairy products (dairy transport truck), vegetables and fruits (fresh goods transport truck), vaccines and drugs (vaccine transport truck), etc.

Structure

A refrigerated truck is composed of the walking part of a dedicated vehicle chassis, as well as insulation and thermal insulation compartment (usually made of polyurethane material, fiberglass, color steel plate, stainless steel, etc.), refrigeration unit, temperature recorder for refrigerated trucks inside the compartment, and other components. For vehicles with special requirements, such as meat hook trucks, optional accessories such as meat hooks, waist guards, aluminum alloy guide rails, ventilation ducts, etc. can be installed.

Manufacturing Technology of Refrigerated Carriage Body

1. The "sandwich" panel adhesive type assembled in pieces is currently used by large refrigerated truck manufacturers in China, and the refrigerated trucks produced using this technology have high thermal insulation performance.
2. Injection foam type assembled in sections.
3. The overall skeleton is injected with foam.
4. Vacuum adsorption adhesive

Classification of refrigeration units:

Refrigeration units are divided into non independent refrigeration units and independent refrigeration units. Domestic and imported units, etc. Most car models use external refrigeration units, while a few micro refrigerated trucks use internal refrigeration units. For refrigerated trucks with lower temperature requirements, a built-in cold plate (equivalent to an evaporator) can be used in the compartment.

Classified by chassis carrying capacity: micro refrigerated truck, small refrigerated truck, medium refrigerated truck, large refrigerated truck

Classified by carriage type: bread refrigerated truck, box refrigerated truck, semi-trailer refrigerated truck

Important equipment

Refrigerated truck refrigeration unit

Refrigerated truck refrigeration unit: an important equipment that provides a continuous supply of "cold" for refrigerated truck containers. It is usually installed at the top of the front of the container and has an air conditioning like appearance, but has stronger cooling capacity than air conditioners of the same volume.

Refrigeration units are generally divided into two types: independent units and non independent units. The difference is that independent units rely entirely on another unit to generate electricity and maintain operation, while non independent units rely entirely on the engine operation of the entire vehicle to drive the cooling work of the unit.

Selection of refrigeration units for refrigerated trucks.

Generally, different power refrigeration units are selected based on the volume of the refrigerated compartment and the temperature requirements of the transported goods.

Main Technical specification

5 Tons Euro 3 Dongfeng Refrigerator Truck	
Overview	
Name	Dongfeng Refrigerator Truck
Dimension(LxWxH)	5995x2340x3220(mm)
Total Mass	8150Kg
Rated Payload	5000Kg
Kerb Weight	3150Kg
Passenger	3
Approach/Departure Angle	20/12

The Parameters of Chassis	
Manufacture/Model	Dongfeng/EQ1060TJ20D3
Driving Type	4*2 left/right hand drive
Wheel Base	3300 mm
Gearbox	Six speed lever with five speed forward and one reverse, manual
Front/Rear Track	1506/1466(mm)
Tyre	7.00R16
The Number of Tyre	6+1 (spare tyre)
Front/Rear Suspension	1032/1658(mm)
Leaf Spring Number	8/9+5, 6/8+4
The Parameters of Engine	
Manufacturer/Model	ChaoChai
Rated Power	82hp
Fuel Type	Diesel oil
Displacement/Capacity	3707ml
Emission Standard	Euro 3
Cylinder	Straight/4/watercooling
Max. torque	235N.m
Velocity	3200rpm
The Parameters of Equipment	
Color/LOGO	Customizable
Box Dimension	4050x2100x2100(mm)
Material	Sandwiched PUF with Fibreglass
Thickness	8 cm
Floor	Checkered aluminum
Skeleton	Aluminum
Doorframe and locks	Stainless Steel
Refrigerator Unit	-15 degree
AC,Power Steer,Power Window,Central Locking	Equipped

5T Dongfeng Refrigerator Van Truck Picture



ITRUCK
SPECIAL VEHICLES

Hubei iTruck Import and Export Trading Co., Ltd

☎ 0086 19947597881

✉ alex@hbitruck.com

🌐 hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,
QINGSHAN DISTRICT, WUHAN