for more products please visit us on hbitruck.com

4x2 Chinese Dongfeng 10000 liters Vacuum Sewage Clean and Suction Truck With Water Tank and Sewage Tank

Basic Information

Place of Origin: HubeiBrand Name: DongfengCertification: ccc

Model Number: CL5120GQW6HQ

Minimum Order Quantity: 1

• Price: 26800\$

Packaging Details: nude with waxing
 Delivery Time: 30-35 working days
 Payment Terms: T/T, D/P, L/C
 Supply Ability: 50 units per month



Product Specification

Name: Dongfeng Sewage Clean And Suction Truck

7000 Liters Sewage Tank: • Total Amount: 12000 Kg Driving Type: 4x2 3800 Mm • Wheelbase: 6TS55 Gearbox: Tvre Model: 7.50/R16 • Engine Model: YC4E135 33 Rated Power: 100kw/135hp • Displacement/Capacity: 4257 MI Vacuum Suction Pump: SK-12 Clean Water Tank: 3000 Liters

Highlight: 4x2 Vacuum Sewage Clean Truck,
 10000 liters Vacuum Sewage Clean Truck
 Water Tank Vacuum Sewage Clean Truck



More Images











Product Description

10 cbm Chinese Dongfeng Combine Sewage Clean and Suction Truck

The cleaning and suction truck has the functions of flushing, dredging, suction, and reverse discharge. The function of a sewage suction truck:

The cleaning and suction truck is a new type of environmental sanitation vehicle used for collecting, transferring, and cleaning the transportation of sludge and sewage. It has the function of self suction and self discharge, and its advantages are fast working speed, large capacity, and convenient transportation. It is suitable for collecting and transporting liquid substances such as feces, mud, crude oil, etc.

The working principle of cleaning the suction truck:

The working principle of cleaning and suction trucks is mainly based on the siphon principle. When the fecal suction hose is submerged under the liquid surface and air is sucked in, the pressure inside the tank will gradually decrease due to the inability to be replenished, causing the fecal liquid to enter the tank through the fecal suction hose under atmospheric pressure. In addition, when the siphon tube approaches the bottom of the tank, air is continuously discharged into the tank. As the air cannot be discharged, the pressure inside the tank will increase, and the feces will be discharged outside the tank through the siphon tube and suction hose under the action of compressed air.

Main Technical specification

Overview	
	10 cbm Dongfeng Sewage Clean and
	Suction Truck
Dimension(LxWxH)	7000x2350x3000 mm
Total Mass	12000 kg
Rated Payload	5720 kg
Kerb Weight	6140 kg
Passenger	3
Approach/Departure Angle	17°/10 °
The Parameters of Chassis	
Manufacture/Model	Dongfeng
Driving Type	4x2
Wheel Base	3815 mm
Gearbox	6TS55
Front/Rear Track	2060/1855 mm
Tyre model	7.50R16
The Number of Tyre	6+1 (spare tyre)
Front/Rear Suspension	1370/2710 mm
The Paremeters of Engine	
Manufacturer/Model	YC4E135 33
Rated Power	100kw/135hp
Fuel Type	Diesel oil
Displacement/Capacity	4257 ml
Emission Standard	Eu 3
Cylinder	4
Max. Torque/ speed	392 N.m/ 1700rpm
Velocity	2800 rpm
The Parameters of Equipment	
Color/Logo	Customizable
Volume of Clean Water Tank	10,000 liters
Volume of Clean Waste Water Tank	10,000 liters
Function	High pressure water pump clean waster
	sluge and vacuum pump suction waste
	water waste garbage
Standard configuration	Install Tongjie/Pinfu 215 flow high-pressure
	pump, with 6 thick tanks, Shandong Zibo
	SK-12 water ring pump, Tianjin SK-15 water
	ring pump, a 100 and 150 ball valve, with
	water and sewage interconnection, air
	blowing water, pipe sprinkler, lifting function,
	rear cover can be opened, install 60 meter 19 # high-pressure pipe, an 8-meter suction
	pipe, and 10 combination nozzles
	pipo, and to combination nozzies

Dongfeng Sewage Suction Picture













Combine Sewage Clean and Suction Truck Stock













Export













Hubei iTruck Import and Export Trading Co., Ltd









ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD, QINGSHAN DISTRICT, WUHAN