

## 4x2 Chinese Dongfeng 6000 Liters Sewage Suction Truck

Our Product Introduction

for more products please visit us on hbitruck.com

### Basic Information

- Place of Origin: Hubei
- Brand Name: Dongfeng
- Certification: CCC
- Model Number: CL5250GXW6HQ
- Minimum Order Quantity: 1
- Price: 45200\$
- Packaging Details: nude with waxing
- Delivery Time: 30-35 working days
- Payment Terms: T/T, D/P, L/C
- Supply Ability: 50 units per month



### Product Specification

- Name: Dongfeng Sewage Suction Truck
- Sewage Tank: 15000 Liters
- Total Amount: 25000 Kg
- Driving Type: 6x4
- Wheelbase: 4500 +1350 Mm
- Gearbox: 12JSD180T
- Tyre Model: 315/80R22.5
- Engine Model: ISLe375 30
- Rated Power: 275Kw, 375Hp
- Displacement/Capacity: 8900 MI
- Vacuum Suction Pump: Zibo Haosai 2BE204
- Highlight: Chinese Dongfeng Sewage Suction Truck, 6000 Liters Sewage Suction Truck, 4x2 Sewage Suction Truck



### More Images



### Product Description

#### 15 cbm Chinese Dongfeng Sewage Suction Truck

The cleaning and suction truck has the functions of flushing, dredging, suction, and reverse discharge.

The function of a sewage suction truck:

The cleaning and suction truck is a new type of environmental sanitation vehicle used for collecting, transferring, and cleaning the transportation of sludge and sewage. It has the function of self suction and self discharge, and its advantages are fast working speed, large capacity, and convenient transportation. It is suitable for collecting and transporting liquid substances such as feces, mud, crude oil, etc.

The working principle of cleaning the suction truck:

The working principle of cleaning and suction trucks is mainly based on the siphon principle. When the fecal suction hose is submerged under the liquid surface and air is sucked in, the pressure inside the tank will gradually decrease due to the inability to be replenished, causing the fecal liquid to enter the tank through the fecal suction hose under atmospheric pressure. In addition, when the siphon tube approaches the bottom of the tank, air is continuously discharged into the tank. As the air cannot be discharged, the pressure inside the tank will increase, and the feces will be discharged outside the tank through the siphon tube and suction hose under the action of compressed air.

Our Product Introduction

#### Main Technical specification

Overview	
Name	15 cbm Dongfeng Suction Truck
Dimension(LxWxH)	9600×2500×3850 mm
Total Mass	25000 kg
Rated Payload	11300 kg
Kerb Weight	13700 kg
Passenger	3
Approach/Departure Angle	17°/10 °
The Parameters of Chassis	
Manufacture/Model	Dongfeng
Driving Type	6x4
Wheel Base	4500+1350 mm
Gearbox	12JSD180T
Front/Rear Track	2060/1855 mm
Tyre model	315/80R22.5
The Number of Tyre	10+1 (spare tyre)
Front/Rear Suspension	1370/2710 mm
The Parameters of Engine	
Manufacturer/Model	ISLe375 30
Rated Power	275Kw, 375Hp
Fuel Type	Diesel oil
Displacement/Capacity	8900 ml
Emission Standard	Eu 3
Cylinder	6
Max. Torque/ speed	1550 N.m/ 1100-1400 rpm
Velocity	2100 rpm
The Parameters of Equipment	
Color/Logo	Customizable
Volume of Clean Waste Water Tank	15,000 liters
Standard configuration	<ol style="list-style-type: none"> <li>1. The tank has a volume of 15 cubic meters and is made of high quality steel plate. The wall thickness is 8mm. The middle of the tank is reasonably designed with a wave plate</li> <li>2. Install Shandong Zibo Haosai 2BE204 water circulating pump</li> <li>3. Install the overflow valve, and install stainless steel filter screen on the vacuum pipe (to prevent impurities from entering the pump)</li> <li>4. A shock resistant pressure gauge with a diameter of 100 is installed at the four-way dirt suction valve, which can resist the vibration of the working environment and reduce the pulsation effect of the medium pressure</li> <li>5. A 100 suction port, a 600 hydraulic drain port at the tail, and a 100 drain port</li> <li>6. The tank body is equipped with lifting and self unloading function, and the drain outlet at the tail can be opened hydraulically with locking device</li> <li>7. The tank top is designed as a platform with protective railings and 2 tank openings installed to facilitate feeding from the top and cleaning the tank</li> </ol>

Dongfeng Sewage Suction Picture



Combine Sewage Clean and Suction Truck Stock



### Export



**ITRUCK**  
SPECIAL VEHICLES

Hubei iTruck Import and Export Trading Co., Ltd

☎ 0086 19947597881

✉ alex@hbitruck.com

🌐 hbitruck.com

ROOM B1084 FLOOR 9TH-14TH, BUILDING A, BAOYE CENTER, NO. 31ST, JIANSHE FIRST ROAD,  
QINGSHAN DISTRICT, WUHAN