

4x2 Chinese Dongfeng 6000 Liters Sewage Suction Truck

Place of Origin:Brand Name:

Basic Information

- Certification:
 - 1:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- Supply Ability.

Dongfeng ccc

Hubei

- CL5180GXW6HQ 1 29700\$ nude with waxing 30-35 working days T/T, D/P, L/C
- 50 units per month



Product Specification

- Name:
- Sewage Tank:
- Total Amount:
- Driving Type:
- Wheelbase:
- Gearbox:
 - 0.00.00/11
- Tyre Model:Engine Model:
- Rated Power:
- Displacement/Capa
- Vacuum Suction Pump:
- Highlight:

	Chinese Dongfeng Sewage Suction Truck, 6000 Liters Sewage Suction Truck
Pump:	SK15
bacity:	5900 MI
	140Kw, 190Hp
	B190-33
	10.00R20
	9JSD180T
	4700 Mm
	4x2
	18000 Kg
	10000 Liters

4x2 Sewage Suction Truck

Dongfeng Sewage Suction Truck



More Images



Product Description

10 cbm Chinese Dongfeng Sewage Suction Truck

The cleaning and suction truck has the functions of flushing, dredging, suction, and reverse discharge. The function of a sewage suction truck:

The cleaning and suction truck is a new type of environmental sanitation vehicle used for collecting, transferring, and cleaning the transportation of sludge and sewage. It has the function of self suction and self discharge, and its

advantages are fast working speed, large capacity, and convenient transportation. It is suitable for collecting and transporting liquid substances such as feces, mud, crude oil, etc.

The working principle of cleaning the suction truck:

The working principle of cleaning and suction trucks is mainly based on the siphon principle. When the fecal suction hose is submerged under the liquid surface and air is sucked in, the pressure inside the tank will gradually decrease due to the inability to be replenished, causing the fecal liquid to enter the tank through the fecal suction hose under atmospheric pressure. In addition, when the siphon tube approaches the bottom of the tank, air is continuously discharged into the tank. As the air cannot be discharged, the pressure inside the tank will increase, and the feces will be discharged outside the tank through the siphon tube and suction hose under the action of compressed air.

Main Technical specification

Overview			
Name	10 cbm Dongfeng Suction Truck		
Dimension(LxWxH)	8200×2500×3550 mm		
Total Mass	18000 kg		
Rated Payload	8900 kg		
Kerb Weight	9100 kg		
Passenger	3		
Approach/Departure Angle	17°/10 °		
The Parameters of Chassis			
Manufacture/Model	Dongfeng		
Driving Type	4X2		
Wheel Base	4700 mm		
Gearbox	9JSD180T		
Front/Rear Track	2060/1855 mm		
Tyre model	10.00R20		
The Number of Tyre	6+1 (spare tyre)		
Front/Rear Suspension	1370/2710 mm		
The Paremeters of Engine			
Manufacturer/Model	B190-33		
Rated Power	140Kw, 190Hp		
Fuel Type	Diesel oil		
Displacement/Capacity	5900 ml		
Emission Standard	Eu 3		
Cylinder	6		
Max. Torque/ speed	650 N.m/ 1500 rpm		
Velocity	2500 rpm		
The Parameters of Equipment			
Color/Logo	Customizable		
Volume of Clean Waste Water Tank	10,000 liters		
Standard configuration	 The tank has a volume of 10 cubic meters and is made of high quality steel plate. The wall thickness is 6mm. The middle of the tank is reasonably designed with a wave plate Install SK-15 water circulating pump Install the overflow valve, and install stainless steel filter screen on the vacuum pipe (to prevent impurities from entering the pump) A shock resistant pressure gauge with a diameter of 100 is installed at the four-way dirt suction valve, which can resist the vibration of the working environment and reduce the pulsation effect of the medium pressure A 100 suction port, a 600 hydraulic drain port at the tail, and a 100 drain port The tank body is equipped with lifting and self unloading function, and the drain outlet at the tail can be opened hydraulically with locking device The tank top is designed as a platform with protective railings and 2 tank openings 		
	installed to facilitate feeding from the top and cleaning the tank		

Dongfeng Sewage Suction Picture



Combine Sewage Clean and Suction Truck Stock













Export

