10 wheels 6X4 ISUZU truck with 20000 liter stainless steel milk tanker

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T, L/C
- Supply Ability:



Product Specification

- Product Name:
- Volume:
- Chassis Model:
- Engine:
- Wheelbase:
- Function:
- Drive Model:
- Tire:
- Transmission:
- Emission Standard:
- Water Tank Material:

- Milk Tanker Truck 20000 Liters
- ISUZU, Optional DFAC,HOWO,SHACMAN,FAW

300HP

Hubei

ISUZU

ISO

FVZ

45 days

\$81300 per unit nude with waxing

50 units per month

1

- 4650+1370 Mm
 - Transport Fresh Milk
 - 6x4
- 295/80R22.5
- 9-speed, Manual
- d: Euro 6
 - Carbon Steel Or Stainless Steel



More Images



Our Product Introduction

Product Description

10 wheels 6X4 ISUZU truck with 20000 liter stainless steel milk tanker.







Main specification :

Complete Vehicle Parame	eter
Vehicle	ISUZU milk tanker truck
Manufacturing year	2025 - the latest, brand new
Overall dimensions (mm)	10200 x 2500 x 3150
Milk tanker (L)	20000
Gross Vehicle Weight (kg)	Appro × 31625
Net weight (kg)	Appro × 11430
Loading (kg)	Appro × 20000
Wheel base (mm)	4650 + 1370
Max speed (km/h)	90
ISUZU Truck Chassis Par	ameter
Cabin	FVZ cabin, a sleeper, power steering, A/C,central lock, electric window, 3 passengers, left hand drive.
Traction system	6×4
Engine	Brand:ISUZU Model: 6HK1-TCG60
	Engine power : 300hp Type: diesel, 6 cylinder, turbocharged,DPF. Displacement: 7.8L Emission standard : Euro 6
Transmission	9 forward, 1 reverse, manual operated
Tire model	295/80R22.5
No.of tires	10+1pcs
Milk Tanker Parameter	. · ·
Standard configuration	 Capacity: 20000 liters. Inside material: food grade stainless steel 304-2B, thick 4mm. Outside: stainless steel mirror finish, thick 2mm. The insulation layer is 80mm thick polyurethane. Divided into 4 compartments, each compartment has CIP cleaning and steam cleaning. Equipped with stainless steel pump, to load and unload milk. Finish: the interior of the milk tank is very smooth and high polished, so it have not any sharp angles. Outlet: butterfly valve at the rear of milk tank.
	 9. Inlet: butterfly valve with a union end. 10. Manhole: with fixes deep stick to the manhole and 430 mm diameter. 11. Accessories: stainless steel ladder to the top of milk tank and anti slippery walkway .

